



Outdoor refreshment

The Outdoor, IP34 certified waterproof version of SandenVendo's popular G-Drink model combines all the utmost innovations of a premium automatic vending machine with the newly-developed features required for outdoor usage including an anti-condensation heated glass, a roof and an anti-vandal front door for further protection. Thanks to its thermal-magnetic circuit breaker and its anti-freezing function with temperature control specially designed for outdoor application, G-Drink Outdoor can also operate under below-zero temperature conditions while its LED illumination system serves as an impulse sales ally during shop-closing hours.

DM6 OD

G-Drink Standard 6 Vertical Outdoor

TECHNICAL SPECIFICATIONS	DM6 OD
DIMENSIONS H x W x D (mm)	1875*x 990 x 1010
WEIGHT (NET - Standard machine without options)	350 Kg
NO. OF SELECTIONS PER SHELF	6
NO. OF SHELVES	Standard 5 / Max. 7
NO. OF SELECTIONS	Standard 30 / Max. 42
MAX. CAPACITY (0.33 l CANS)	336
MAX. CAPACITY (0.50 l PET BOTTLES)	240
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
INTERNAL TEMPERATURE RANGE	+2°C up to +10°C
AMBIENT TEMPERATURE RANGE	-15°C up to +32°C
COOLING UNIT	HC2 / HCD
POWER SUPPLY	230/240 V - 50/60 Hz
MAX. POWER CONSUMPTION	490 W
ENERGY CLASS	E
ENERGY CONSUMPTION - kWh/annum	1290
MAX. POWER CONSUMPTION	530 W
ENERGY CLASS	F
ENERGY CONSUMPTION - kWh/annum	2003

*With adjustable leveling screw

© SandenVendo GmbH

Technical data, images and information provided on this document is intended for informational purposes only; All specification are subject to change without notice.



Outdoor refreshment

The Outdoor, IP34 certified waterproof version of SandenVendo's popular G-Drink model combines all the utmost innovations of a premium automatic vending machine with the newly-developed features required for outdoor usage including an anti-condensation heated glass, a roof and an anti-vandal front door for further protection. Thanks to its thermal-magnetic circuit breaker and its anti-freezing function with temperature control specially designed for outdoor application, G-Drink Outdoor can also operate under below-zero temperature conditions while its LED illumination system serves as an impulse sales ally during shop-closing hours.

DM9 OD

G-Drink Standard 9 Vertical Outdoor

TECHNICAL SPECIFICATIONS	DM9 OD
DIMENSIONS H x W x D (mm)	1875* x 1260 x 1010
WEIGHT (NET - Standard machine without options)	410 Kg
NO. OF SELECTIONS PER SHELF	9
NO. OF SHELVES	Standard 5 / Max. 7
NO. OF SELECTIONS	Standard 45 / Max. 63
MAX. CAPACITY (0.33 l CANS)	504
MAX. CAPACITY (0.50 l PET BOTTLES)	360
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
INTERNAL TEMPERATURE RANGE	+2°C up to +10°C
AMBIENT TEMPERATURE RANGE	-15°C up to +32°C
COOLING UNIT	HC2 / HCD
POWER SUPPLY	230/240 V - 50/60 Hz
MAX. POWER CONSUMPTION (HCD)	490 W
ENERGY CLASS (HCD)	E
ENERGY CONSUMPTION - kWh/annum (HCD)	1700
MAX. POWER CONSUMPTION (HC2)	530 W
ENERGY CLASS (HC2)	F
ENERGY CONSUMPTION - kWh/annum (HC2)	2584

*With adjustable leveling screw

© SandenVendo GmbH

Technical data, images and information provided on this document is intended for informational purposes only; All specification are subject to change without notice.