



# PR39

*Load-bearing rail for decking.*

## PR39

REF	DESCRIPTION	QTY/PALLET	COMPATIBILITY
1194	<b>PR39 - 124</b> 32 clips for 16 boards of 120 mm. 39 x 55 x <b>1984</b> mm.	108 pcs	Accoya®, Kebony®, Moso®, Thermo-Ash, Thermo-Pine
1194	<b>PR39 - 124</b> 64 clips for 32 boards of 120 mm. 39 x 55 x <b>3968</b> mm.	108 pcs	
2034	<b>PR39 - 145</b> 26 clips for 13 boards of 140 mm. 39 x 55 x <b>1885</b> mm.	108 pcs	UPM
1193	<b>PR39 - 150</b> 26 clips for 13 boards of 145 mm. 39 x 55 x <b>1950</b> mm.	108 pcs	Nekko
1861	<b>PR39 - 155,5</b> 24 clips for 12 boards of 150 mm. 39 x 55 x <b>1866</b> mm.	108 pcs	Dex
1781	<b>PR39 WITHOUT CLIPS</b> For tapered boards. 39 x 55 x <b>1984</b> mm.	108 pcs	

## TECHNICAL CHARACTERISTICS

<b>Rail material</b>	Aluminium 6060
<b>Rail finish</b>	Black paint
<b>Clip material</b>	Polyoxymethylene (POM)
<b>Rail weight (including clips)</b>	+/- 1,40 kg/m
<b>Maximum Length</b>	3968 mm
<b>Pull-out strength of the clip on the rail</b>	150 to 250 kg, for two clips (depending on the type of board)

- Load-bearing rail, pedestal spacing up to 70 cm for private use.
- Clips are factory-placed onto the rail for perfect drainage lines
- Each board can be removed individually with dismantling keys adapted to the width of the board
- Rail can be cut to length
- No contact between the boards and the aluminium rail for better air flow
- Invisible fastening
- Simple, quick and ergonomic installation
- Endless possibilities
- 100% recyclable
- Taylor-made rails on demand: for your specific project, custom rails can be designed and produced. Feasibility and conditions on request. Minimum quantity per order to be advised.