



User Manual

CAM-11

Universal Trajectory Camera
Surface Mount

PRODUCT FEATURES:

Image Sensor: 1099 HD CCD
TV Lines: 480
Resolution: 976 x 496
Lumen: 0.1 Lux
Horizontal Angle: 170 Degrees
Vertical Angle: 120 Degrees
TV System: NTSC
Video Output: 1.0V p-p 75ohm
Operating Voltage: 12V DC (Negative Ground)
Current Consumption: 40mA @ 13.8V
Operating temperature: -20 Degrees C to +70 Degrees C
Waterproof Rating: IP68
Parking Lines: Yes (Tracking Lines)
Removable Lines & Image Adjustment: Yes
Enhanced Performance In Low Light: Yes

DISCLAIMER:

Prior to Installation

Read the manual prior to installation. Technical knowledge is necessary for installation. Please ensure you use the correct tools to avoid damage to the vehicle or product.

Connects2 can not be held responsible for the installation of this product.

Technical Support

Connects2 want to provide a fast and suitable resolution should you encounter any technical issues. With this in mind, when contacting Connects2, try to provide as much Information as possible. This will speed up the process and help us to help you.

Please use our dedicated online technical support centre: support.connects2.com

- Camera with adjustable mounting bracket a 1m cable to mini Male 4 pin connector
- 1.3m camera connection cable with mini Female 4 pin connector and RCA Female connector
- 6m RCA Male to Male extension cable
- Instructions

INSTALLATION

1. Connect the Black wire to a suitable ground and the Red wire to a switched +12V supply.
2. If the camera is to be used in the rear of the vehicle, the Red wire should be connected to the reversing light circuit or an interface which provides a reverse signal.
3. Select a suitable location for the camera and ensure that the area is free from all cables, fuel & oil.
4. Whenever possible, avoid locations that are subject to road dirt & water spray.
5. Using the supplied mounting bracket, mount the camera in the required position and connect the 1.3m camera connection cable to the to the camera's 1m cable.
6. Connect the RCA extension cable to the camera connection cable and display screen and ensure that the image is displayed correctly.
7. Adjustment of the camera may be required to ensure that the correct angle of the image is achieved.
8. To remove the parking line feature and to swap the image from mirror to normal view, cut the small looped wire which is located on the camera connection cable.



Subscribe to our YouTube Channel for installation guides and tips... www.youtube.com/connects2