



...connecting to the aftermarket

Connects2 Vision

User Manual

CAM-3

Rearview CMOS Camera
Pivoting, Surface Mounted (Vertical
Adjustment) with White Housing

PRODUCT FEATURES:

Sensor: 1/4" (6.35mm) CMOS
Current Consumption: 106mA @ 13.8V
Resolution: (TV Lines) 480
Minimum Illumination: 0.1 Lux
Angle: 170 Degrees
Effective Pixels: 648 x 488
TV system: NTSC
Video Output: 1.0V p-p 75ohm
Parking Lines: Yes
Working Voltage: DC9-16V (Negative Ground)
Operating Temperature: -30 Degrees C to +65 Degrees C
Waterproof Rating: IP67
Infra-Red LED's: No
Image: Mirror
Enhanced Performance In Low Light: Yes

DISCLAIMER:

Prior to Installation

Read the manual prior to installation. Technical knowledge is necessary for installation. Please ensure you use the correct tools to avoid damage to the vehicle or product.

Connects2 can not be held responsible for the installation of this product.

Technical Support

Connects2 want to provide a fast and suitable resolution should you encounter any technical issues. With this in mind, when contacting Connects2, try to provide as much information as possible. This will speed up the process and help us to help you.

Please use our dedicated online technical support centre: support.connects2.com

- Camera with adjustable mounting bracket and 1m cable to RCA Female video connector and Female DC connector
- 2.5m DC power cable with Male DC connector
- 6m RCA Male to Male extension cable
- Instructions

INSTALLATION

1. Connect the Black wire to a suitable ground and the Red wire to a switched +12V supply.
2. If the camera is to be used in the rear of the vehicle, the Red wire should be connected to the reversing light circuit or an interface which provides a reverse signal.
3. Select a suitable location for the camera and ensure that the area is free from all cables, fuel & oil.
4. Whenever possible, avoid locations that are subject to road dirt & water spray.
5. Remove the protective backing from the adhesive pad and place the camera in the required position.
6. Using the supplied video cable, connect the camera to the display screen and ensure that the image is displayed correctly.
7. Adjustment of the camera may be required to ensure that the correct angle of the image is achieved.



Subscribe to our YouTube Channel for installation guides and tips... www.youtube.com/connects2