

King Kombo Industrial



Specifications

- Brand: Little Giant Ladder Systems
- Warranty: 1-year
- Max Load: 150kg
- Standard: EN131 PROFESSIONAL
- Material: GRP Fibreglass/Aluminium
- Commodity Code: 39269097
- Country of Origin: CN
- Recommended Usage: Intensive

Common Dimensions

- Rung Depth: 80mm
- Distance Between Rungs: 300mm

Availability & Delivery

- Stock item. Delivery next day. (See exceptions, if applicable, overleaf)

[Representative image of product]

Product Description

Little Giant's King KomboTM Industrial is the world's first and only 3-in-1 extension ladder, leaning ladder and stepladder combination, in one lightweight package. King KomboTM was built for those who get stuff done! King KomboTM, with ultra-heavy-duty feet, seriously aggressive tread for elite traction and durability for harsh industrial environments. King KomboTM also brings a tough corner, pole, and stud gripping V-bar for the extension ladder position. This heavy-duty grip conforms to inside and outside corners and even offers protection for damageable leaning surfaces like paint, drywall, and stucco and round poles. Speed, power, and safety prepare to be faster and safer than ever on the job! Fitted with the patent-pending Ground CueTM, an audible and tactile signal to let you know you when you have reached the bottom step of the ladder.

Features

- Ultra-heavy-duty feet with aggressive tread for elite traction & fitted with Ground CueTM on the bottom tread

- Tough corner, pole and stud gripping V-bar for the extension ladder position

- Heavy-duty grip conforms to inside and outside corners and even offers protection for damageable leaning surfaces such as paint, drywall and stucco

- Patent-pending non-conductive Hi-Viz green fibreglass makes the ladder more noticeable
- Wide-flared side offers superior side-tip stability
- Straight side allows operators to access tight work spaces between stud gaps, ceiling trusses and attic access ports
- This ladder brings speed, power and safety to any job with palm buttons for easy adjustment

Please note that products marked 'Special Order' cannot be cancelled and are non-returnable once orders are acknowledged and placed. This document is presented as a guide only; It is subject to change without notice and as such is not legally binding, nor does it form part of any contract.



King Kombo Industrial

Product Dimensions

SKU	Rungs /Sections		Last Climbing Height	Approx. Working Height ¹ (mm)		Extended Length (mm)	Closed Length (mm)		Storage Width (mm)	Storage Depth (mm)		Nett Weight (kg)
1303-205	5 + 4		1430	3380		2900	1550		620	180		10.4
1303-206	6 + 4		2010	3960		3020	1850		640	180		10.4
1303-208	8+6		3250	5200		4240	2460		710	180		14.1
SKU		Max. Step Height (mm)			Approx. Working Height ¹ (mm)			Open Step Depth (mm)		Open Step Height (mm)		
1303-205		860			2810			910		1500		
1303-206		1140			3090			1120		1800		
1303-208		1730			3680			1500			2400	

¹ Working Height is an approx. calculation of 1,950mm plus platform height or last climbing tread, whichever is appropriate. Ladders set at angle of ~75° degrees.

Shipping Dimensions

SKU	Shipping Length (mm)	Shipping Width (mm)	Shipping Depth (mm)	Shipping Volume (m ³)	Gross Weight (kg)
1303-205	1575	635	178	0.178	12.2
1303-206	1880	635	178	0.212	12.7
1303-208	2464	686	178	0.301	17.7

Packaging Material — Heavy-duty Cardboard Box

Please note that products marked 'Special Order' cannot be cancelled and are non-returnable once orders are acknowledged and placed. This document is presented as a guide only; It is subject to change without notice and as such is not legally binding, nor does it form part of any contract.