

4 Rung Little Giant All-Terrain Conquest GRP



[Representative image of product]

Product Description

Access a variety of workspaces with the GRP Fibreglass Little Giant Conquest ladder. This versatile, multi-position ladder will help you get stuff done efficiently.

1. SIDE-MOUNTED STABILISING LEGS

Grip and squeeze the side mounted legs, which are independent, to level the ladder on rough or uneven ground.

2. PATENTED RAPID LOCK

Grip and twist the Rapid Lock, then slide the ladder rails to the desired size. Twist the Rapid Lock once more to lock the ladder in place.

3. PALM BUTTONS

Move from storage to A-frame, extension and 90-degree configurations by pushing the ladder's palm buttons.

4. TIP & GLIDE WHEELS

The integrated Tip & Glide wheels help you move the ladder quickly from job to job.

V-Bar

The extension side of the ladder is narrow enough to access tight spaces between wall studs, ceiling trusses and roof or attic access ports and can be safely set up on poles or outside corners. The wall pad feet are designed for inside corners and flat walls without damage to the surface.

Carrying Handle

Weight-balanced carrying handle simplifies the transportation of the ladder.

Features

- Same HiViz Insulated Stiles as the King Kombo
- Side-mounted independent stabilisers allow use on rough or uneven ground
- Features A-frame, Extension and 90-degree Step configurations
- Fitted with V-Bar for use on Telegraph Poles
- Carry handle & wheels fitted for easy transport

Specifications

- Brand: Little Giant Ladder Systems
- Warranty: 1-year
- Max Load: 150kg
- Standard: EN131-4:2020 PROFESSIONAL
- Material: Fibreglass
- Commodity Code: 39269097
- Country of Origin: CN
- Recommended Usage: Intensive

Common Dimensions

- Rung Depth: 25mm
- Distance Between Rungs: 297mm

Availability & Delivery

- Stock item. Delivery next day.

4 Rung Little Giant All-Terrain Conquest GRP

Product Dimensions

SKU	Rungs /Sections	Last Climbing Height (mm)	Approx. Working Height ¹ (mm)	Extended Length (mm)	Closed Length (mm)	Storage Width (mm)	Storage Depth (mm)	Nett Weight (kg)
1304-044	4 x 4	3530	5480	2720–4550	1400	610	610	19.4

SKU	Max. Step Height (mm)	Approx. Working Height ¹ (mm)	Open Step Depth (mm)	Open Step Height (mm)
1304-044	1470	3420	1030–1580	1370–2290

¹ Working Height is an approx. calculation of 1,950mm plus platform height or last climbing tread, whichever is appropriate. Ladders set at angle of ~75° degrees.

Shipping Dimensions

SKU	Shipping Length (mm)	Shipping Width (mm)	Shipping Depth (mm)	Shipping Volume (m ³)	Gross Weight (kg)
1304-044	1430	635	240	0.218	21.4

Packaging Material — Cardboard Carton

Please note that products marked '**Special Order**' cannot be cancelled and are non-returnable once orders are acknowledged and placed.

This document is presented as a guide only; It is subject to change without notice and as such is not legally binding, nor does it form part of any contract.

TB Davies (Cardiff) Ltd, Lewis Road, Cardiff, CF24 5EB, GB. +44(0)29 2132 0000 www.tbdavies.co.uk Registered in England No.534073, VAT Reg. No.GB134144207
Awarded Silver by Investors in People, 2018. An ISO 9001 Registered Company. Members of The Ladder Association and PASMA.

2023-10-18 14:31:44