



Revision #	Revision Date					
# O	18/01/2023					

Lockinex great service, great quality

INTRODUCTION

Tiger Gratings & Stair Treads, Nosings and clips are used as part of access structures and stairways.

Pre manufactured for fast despatch, complimented with part manufactured items for the engineer to cut and weld to their own designs where required.

APPLICATION

Used in the construction of Industrial Access walk ways and Staircases.

COMPOSITION, MANUFACTURE Stair Treads, Nosings and clips are all manufactured form mild steel.

Except for the items part manufactured for the engineer to cut & weld, all other items are galvanised to BS EN 1461:2009









DESIGN

Various designs and sections to accommodate current Building Regulations & BS EN Codes.








Open steel stair treads-Loose End Plate




This product has the same features shown in the drawing above. However this product is supplied with one of the end plates loose and comes with a self-colour finish ready for cutting to length & welding.





Self-colour open steel stair treads with Durbar nosing & loose end plate



This product has the same features shown in the drawing above. However, this product is supplied with one of the end plates loose and comes with a self-colour finish ready for cutting to length & welding.









Perforated steel stair-treads (Can also be used to construct walkways-see below)



Product Code	Α	B1/B2	C	D	Е	F	G	Н	K	Holes
Tiger-01	250	45/57	2	50	15	13	13	17	142	9mm up/5mm down
Tiger-03	250	42/54	2	50	15	13	13	17	142	12mm up/7mm down





Multiple perforated treads, laid in-line to create a walkway.




Underside of walkway showing fixing down clips.




Clip-45 To suit 45mm deep perforated Treads and flooring.





Unbound bearing bars at end



Lockinex multi-fit flooring clip. Galvanised finish complete with nylock nuts. Fits 30mm to 41mm load bar centres and fits up to 50mm deep load bars as standard. Once the clip is assembled, it can be inserted through the grating and with a standard spanner or screw driver tightened. The clever design of the clip holds the nut firmly in place while the operator can safely tighten the bolt from above. The nylock nut keeps the clip firmly in place and prevents any unwanted loosening through vibration etc.

