PIXMA G3770





Wireless Refillable Ink Tank Printer with Low-Cost Printing

The ultimate wireless refillable ink tank printer that combines functionality and style. This high-performance 3-in-1 printer comes with a 1.35" backlight LCD screen making device operation easier.

EASY, HASSLE-FREE INK REFILL

Ink refilling is now made easy. Each ink bottle nozzle is designed to fit seamlessly only into the designated ink tank, eliminating potential mixing accidents.



EASY Maintenance

The easy-to-replace maintenance cartridge makes maintenance fuss-free and extends the printer's lifespan even when printing in high volumes.



GUIDED INSTRUCTIONS ON LCD PANEL

The 1.35" intuitive LCD screen with guided instructions makes device operation and settings easy without having to look at user manuals.



MOBILE AND Cloud Printing

Print from smartphones, tablets, laptops and cloud storage with the Canon PRINT Inkjet/SELPHY and Easy-PhotoPrint Editor apps.







0

CONNECTIVITY



SPECIFICATIONS				PIXMA G3770		
	Maximum Printing Resolution			4,800 (horizontal) ¹¹ x 1,200 (vertical) dpi		
PRINT		ESAT/Simplex (Mono/Colour)		11 / 6 ipm		
	Print Speed ^{*2}	FPOT Ready/Simplex (Mono/Colour)		9 / 14 sec		
		Photo (4 x 6")		45 sec		
SCAN ⁻³	Scanner Type			Flatbed		
	Scanning Method			Contact Image Sensor (CIS)		
	Optical Resolution'4			600 x 1,200 dpi		
	Maximum Document Size			A4, LTR (216 x 297 mm)		
СОРҮ	Copy Speed ^{∙₅}		sFCOT/Simplex	23 sec		
		Colour	sESAT/Simplex	3.2 ipm		
	Maximum Copies			99 pages		
	Maximum Document Size			A4, LTR		
		Plain Paper (64 g/m²)		Up to 100 sheets		
	Maximum Input Capacity	Photo Paper (4 x 6″)		Up to 20 sheets		
PAPER HANDLING	Media Size			A4, A5, A6, B5, LTR, LGL, Executive, Legal, Foolscap, F4, Oficio2, B-Oficio, M-Oficio, Envelope (COM10, DL, C5, Monarch), Card Size (91 x 55 mm), 4 x 6", 5 x 7", 7 x 10", 8 x 10", Square (89 x 89 mm, 127 x 127 mm), Custom (width: 55 – 216 mm, length: 89 – 1,200 mm)		
	Media Type			Plain Paper (64 – 105 g/m²) High Resolution Paper (HR-101N) Photo Paper Plus Glossy II (PP-201, PP-208) Glossy Photo Paper (GP-508) Photo Paper Plus Semi-Gloss (SG-201) Photo Paper Pro Luster (LU-101) Matte Photo Paper (MP-101) Double-Sided Matte Paper (MP-101D) Photo Stickers (PS-208, PS-808) Envelope		
TS	Operating System Compatibility	Please visit https://asia.canon to confirm OS compatibility and to download the latest drivers.		Windows 11 / 10 / 8.1 / 7 SP1'6 macOS 10.14.16 – 12 or later Chrome OS		
	Interface			Wireless LAN IEEE802.11b/g/n/a ^{·7} /ac ^{·7} USB 2.0		
DNEN	Canon Printing Apps	Mobile		Canon PRINT Inkjet/SELPHY, Easy-PhotoPrint Editor, Creative Park		
NETWORK SYSTEM REQUIREMENTS & GENERAL SPECIFICATIONS		Others		Easy Layout Editor, PosterArtist Lite, PosterArtist (Web), Canon Inkjet Smart Connect		
	Mobile/Cloud Printing Solutions			AirPrint, Mopria, Canon Print Service (Android), Direct Wireless PIXMA Cloud Link		
STE L SI	Power			AC 100 – 240 V, 50/60 Hz		
ER A	Power Consumption ^{*8}			16 W (Standby: 0.6 W)		
NETWORK & Gen	Duty Cycle			Up to 3,000 pages/month		
	Recommended Monthly Print Volume			150 – 1,500 pages		
	Operation Panel	Display		1.35" / 3.4 cm LCD (Monochrome)		
		Factory Configuration		416 x 337 x 177 mm		
	Dimensions (W x D x H)	Output/Trays Extended		416 x 557 x 268 mm		
	Weight			6.0 kg		
CONSUMABLES	Ink Bottles	Type/Colours		Pigment Ink / Black Dye-Based Ink / Cyan, Magenta, Yellow		
		Page Yield ^{•9} (A4, Pages)		GI-7I PGBK: 6,000 (Standard) / 7,600 (Economy ^{'11}) GI-71 C, M, Y: 7,700 ^{'10} (Standard) / 8,100 ^{'10} (Economy ^{'11})		
CON	User Replaceable Maintenance Cartridge			MC-G04		

Specifications are subject to change without notice.

*1 Ink droplets can be placed with a pitch of 1/4800 inch at minimum.

² Document print speeds are the averages of ESAT (Word, Excel, PDF) in Office Category Test for the default simplex mode, ISO/IEC 24734. Photo print speed is based on the default setting using ISO/JIS-SCID N2 on Photo Paper Plus Glossy II and does not take into account data processing time on host computer. Print speed may vary depending on system configuration, interface, software, document complexity, print mode, page coverage, type of paper used etc.

^a TWAIN driver (ScanGear) is based on the TWAIN specification V1.9 and requires the Data Source Manager comes with the operating system.

⁴ Optical resolution is a measure of maximum hardware sampling resolution, based on ISO 14473 standard. Optical resolution scan is available only when you use TWAIN Driver.

⁵ Copy speeds are the average of sFCOT and sESAT, ISO/IEC 29183. Copy speeds (ADF) are ESAT of copy in sequence, ISO/IEC24735. Copy speed may vary depending on document complexity, copy mode, page coverage, type of paper used etc. and does not take into account warm up time.



SOUTH AND SOUTHEAST ASIA REGIONAL HEADQUARTERS CANON SINGAPORE PTE. LTD.

1 Fusionopolis Place, #14-10 Galaxis, Singapore 138522

Tel: 65-6799-8888 | Fax: 65-6799-8882 | https://asia.canon

DEALER'S STAMP	This document is for information purposes only. The contents are subject to change without notice. Product options, name and availability may vary by regions. We expressly disclaim any liability or contractual obligations with respect to this document. Brands and product names are trademarks and/or registered trademarks of their respective owners.

*6 Operation can only be guaranteed on a PC with a pre-installed Windows 7 or later.

*8 When copying ISO/JIS-SCID N2 (printed by inkjet printer) on A4 size plain paper using default settings. * Page yield is the estimated value based on Canon individual test method using the ISO/IEC 24712 colour chart and continuous printing simulation with the Standard ink bottles after initial setup. Page yield varies significantly depending on contents printed and other factors.

** The Economy mode reduces the ink consumption by lowering the density. More pages can be printed by using

*7 Wireless LAN IEEE802.11a/ac are available for Taiwan models only.

*10 Based on 1 set of colour bottles

this mode.