



Samsung Mono Laser Printer ML-5510ND/ML-6510ND



Key Features:

- Print Speeds up to 52ppm/62ppm in A4
- First Print Out Time 7.8 seconds (from Ready Mode)
- Improved Print Quality with up to 1,200 x 1,200 dpi
- Maximum Monthly Duty Cycle 275,000 sheets
- Quiet Operation at less than 56dBA (printing)
- Standard Cartridge Yield of 10,000 pages
- Samsung 700MHz processor
- 520-sheet input capacity, 100-sheet multi-purpose tray
- Direct Printing from USB memory
- Secure Printing

Seamless integration for a simple business workflow solution

The Samsung ML-5510ND/ML-6510ND provides hassle-free integration for a simple business workflow solution.

Delivering a business print solution that answers both simplicity and productivity needs can be a challenge, especially across today's diverse business environment. With hassle-free integration and easy-to-use functionality, the Samsung Mono Laser Printer ML-5510ND/ML-6510ND delivers unlimited productivity – simply.

With innovative features and high capacity toner cartridges, the Samsung ML-5510ND/ML-6510ND enables your business to deliver considerable savings on your print costs.

Top 4 Reasons to Buy:

- 1 Value for money**
 - Lower cost per page and fewer toner replacements with extra high yield toner cartridges.
 - Separate toner and drum cartridges allows for a reduction in TCO by replacing the drum unit only when required and not with every new toner cartridge.
- 2 Powerful technology and powerful performance**
 - 700MHz dual-core processor, and 1Gigabit LAN - Enables large size of documents from multiple users to be transmitted and processed fast.
 - Fast printout speeds of up to 62ppm and a First Print Out Time of 7.8 seconds.
- 3 User friendly and reliable**
 - Easy to use 4 line LCD control panel and numeric keypad for effective operation.
- 4 Out-of-box security solution**
 - Secure Job Release with numeric keypad
 - Optional Barcode Printing Solution

Product Configuration



Product Datasheet

Samsung Mono Laser Printer ML-5510ND/ML-6510ND

Product Specifications

ML-5510ND/SEE

ML-6510ND/SEE

| Print | |
|-----------------------------|---|
| Speed (Mono) | Up to 52ppm in A4 (55ppm in Letter) Up to 62ppm in A4 (65ppm in Letter) |
| Resolution | Up to 1,200 x 1,200 dpi effective output |
| First Print Out Time (Mono) | As fast as 7.8 seconds |
| Emulation | PCL5e, PCL6, KS/KSSM, KS5895, IBM ProPrinter, EPSON, PostScript3, PDF Direct V1.7, XPS v1.0 |
| Duplex | Built-in |
| Paper Handling | |
| Input Capacity and Types | 520-sheet Cassette, 100-sheet Multi-Purpose Tray / Max 3,660 Sheet Paper Capacity |
| Output Capacity and Type | 500-sheet Face-Down |
| Media Size | 76mm x 127mm (3" x 5") ~ 216mm x 356mm (8.5" x 14"), (Envelope: Monarch, No10, DL, C5, C6, No9) |
| Media Type | Printer Default, Plain Paper, Thick Paper, Thin Paper, Bond Paper, Colour Paper, CardStock, Labels, Transparency, Envelope, Pre-printed, Recycled Paper, Archive, Extra Thick |
| Envelope Capacity | 50 sheets from Cassette and 50 sheets from optional 1st Second Cassette, (Max. 100 sheets) |
| General | |
| Processor | Samsung 700MHz processor |
| Memory/Storage | 256MB (Max. 768MB) & Optional 160GB Hard Disk Drive |
| OS Compatibility | Windows 2000/XP (32/64bits)/Vista (32/64bits)/2003 Server (32/64bits)/2008 Server (32/64bits)/7 (32/64bits)/2008 Server R2 (64bits) Various Linux OS: RedHat Enterprise Linux WS 4, 5 (32/64 bit) Fedora 4, 5, 6, 7, 8, 9, 10, 11, 12 (32/64 bit) SuSE Linux 10.0, 10.1 (32 bit) OpenSuSE 10.2, 10.3, 11.0, 11.1, 11.2 (32/64 bit) Mandriva 2005, 2006, 2007, 2008, 2009, 2009.1 (32/64 bit) Ubuntu 5.04, 5.10, 6.06, 6.10, 7.04, 7.10, 8.04, 8.10, 9.04, 9.10 (32/64 bit) SuSE Linux Enterprise Desktop 10, 11 (32/64 bit) Debian 4.0, 5.0 (32/64 bit) Mac OS 10.3 ~ 10.6 UNIX OS: Sun Solaris 9, 10 (x86, SPARC) HP-UX 11.0, 11i v1, 11i v2, 11i v3 (PA-RISC, Itanium) IBM AIX 5.1, 5.2, 5.3, 5.4 |
| Interface | Ethernet 10/100/1000 Base TX, High Speed USB 2.0, Host USB 2 Port (Rear 1 Port & Front 1 Port), IEEE 1284B Parallel connector (Option), 802.11 b, g, n wireless network (Option) |
| Noise Level | Less than 56dBA (Printing), Background Noise Only (Less than 30dBA) (Standby) Less than 58dBA (Printing), Background Noise Only (Less than 30dBA) (Standby) |
| Duty Cycle, Monthly | 275,000 sheets |
| Dimension (WxDxH) | 464mm x 540mm x 420mm |
| Weight | 34.8kg (Inc. Imaging Unit/Toner/WTB), 31.2kg (exc. Imaging Unit/Toner/WTB) |
| Power Consumption | 820W(Active)/100W(Ready)/10W(Sleep) 900W(Active)/120W(Ready)/10W(Sleep) |

Consumables

| | |
|-------|---|
| Yield | Standard: Average Cartridge Yield 10,000 standard pages High Yield: Average Cartridge Yield 30,000 standard pages (ships with 10,000 pages Starter Toner Cartridge) Imaging Unit: Average Yield 80,000 standard pages; Declared Cartridge Yield in accordance with ISO/IEC 19752. |
| Type | 2-piece Cartridge (Toner and Imaging Unit (Drum Unit)) |
| Codes | Toner Cartridge: MLT-D309L/ELS - 10,000 Pages,, MLT-D309S/ELS - 30,000 Pages, Imaging Unit: MLT-R309/ELS - 80,000 Pages |

Options

| | |
|---------|--|
| Options | 520 Sheet Paper Tray - ML-S6510A/SEE 2,000 Sheet High Capacity Feeder - ML-H6510A/SEE Short Stand - ML-DSK65S/SEE 512mb Memory - ML-MEM170/SEE 160GB Hard Disk Drive - ML-HDK465/SEE 500 Sheet Staple Finisher - ML-OCT65/SEE 400 Sheet 4 Bin Mailbox - ML-MBT65/SEE Wireless Network Card - ML-NWA65L/SEE IEEE 1284B Parallel Connector - ML-PAR100/SEE Barcode Solution - SOL-BPSV1/SEE |
|---------|--|



For more information, please visit www.samsung.com/uk/printer

SAMSUNG