



(CB5011) Removable Mud-In Flush Mount Wall Air Return, 6" x 6" (Drywall Opening)



GENERAL SPECIFICATIONS:

- Removable Air Return Vent for duct opening (if applicable)/or wall cavity size 6" x 6"
- Overall Dimensions: 8.475" x 8.375" x 0.5"
- Vented Opening Dimensions: 3.75" x 3.75"
- Fits into a Drywall Opening of 6" x 6"

APPLICATION:

- Designed to be installed with 1/2" or 5/8" thick drywall
- Install anywhere on a wall where there are duct openings (if applicable) both high (towards the ceiling) or low (towards the floor)

FEATURES:

- Impact resistant Triple Fibre Reinforced Cement Board
- Easy installation
- Primed vent ready to accept paint
- Machine beveled outer edges to allow for air nails or screws, joint tape, and drywall compound
- Made of non-flammable materials
- Moisture, mold, and water resistant

PRODUCT SPECIFICATIONS:

- Each slot size - 3.75" x 0.32"
- 6 straight horizontal vent slots
- Over 6 square inches (38.706 Sq cm) of open vent area

MATERIAL SPECIFICATIONS:

Raw Material: Cement, fibres, quartz sand, non-hazardous fillers

Density: $1.0 < D \leq 1.2 \text{ g/cm}^3$

Asbestos Content: 100% asbestos-free

Fire resistance: non-combustible

Water Absorption: $\leq 40\%$

Resistant Bending Strength: $\leq 10.5 \text{ MPa dry}$

Moisture Movement: 0.25 %

Freeze Thaw: No distortion after 25 repeated cycles of freezing and thawing

