

info@envisivent.com

🔇 (905) 669-6336

# Spec Sheet

## (CB5018) 14" x 8" (Drywall Opening) Removable Mud-In Flush Mount Air Return

### **GENERAL SPECIFICATIONS:**

- Mud-in/ Tapeable Air Return Vent for drywall opening size 14" x 8"
- Overall Dimensions: 16" x 10".5 x 0.5"
- Vented Opening Dimensions: 11.5" x 6"

#### APPLICATION:

- Designed to be installed with <sup>1</sup>/<sub>2</sub>" thick drywall
- Install anywhere on a wall where there are duct openings (if applicable) both high (towards the ceiling) or low (towards the floor)
- Permanent installation once installed the air return vent cannot be removed

#### FEATURES:

- Impact resistant Triple Fibre Reinforced Cement Board
- Easy installation
- · Primed vent ready to accept paint
- Machine beveled outer edges to allow for air nails or screws, joint tape, and drywall compound
- Made of non-flammable materials
- · Moisture, mold, and water resistant

#### **PRODUCT SPECIFICATIONS:**

- Each slot size 5.805" x 0.32"
- $\cdot$  18 straight horizontal vent slots
- $\cdot$  Over 27 square inches of open vent area

#### MATERIAL SPECIFICATIONS:

**Raw Material:** Cement, fibres, quartz sand, non-hazardous fillers

**Density:** 1.0<D ≤1.2 g/cm3

Asbestos Content: 100% asbestos-free

Fire resistance: non-combustible

Water Absorption: ≤40%

**Resistant Bending Strength:** ≤10.5 MPa dry

Moisture Movement: 0.25 %

**Freeze Thaw:** No distortion after 25 repeated cycles of freezing and thawing

