

Spec Sheet

(CB5071) – Removable Magnetic Mud-In Flush Mount Air Supply, 5" Round



GENERAL SPECIFICATIONS:

- Magnetic Mud-In/ Tapeable Air Return Vent Cover for 5" diameter duct
- Fits into a drywall opening of 10.25" x 10.25" (260.35mm x 260.35mm)
- Overall Dimensions: 10" x 10" x 0.54" (254mm x 254mm x 13.7mm)
- Vent Cover Dimensions: 5" diameter
- Vented Opening Area: 9.14 square inches (58.96 square centimeters)

APPLICATION:

- Designed to be installed with $\frac{1}{2}$ (12mm) or $\frac{5}{8}$ (16mm) thick drywall
- Suitable for both wall and ceiling installation
- Screws directly to your framework (studs or joists) to allow it to be flush

FEATURES:

• Magnetic Removable Impact Resistant Triple Fibre Reinforced Cement Board Vent Cover

- · Primed vent cover ready to accept paint
- · 20 degree angled vent slots for directional venting
- 18 gauge galvanized satin coat adjustable diffuser
- 4 magnetic tabs on Vent Cover for easy removal
- Made of non-flammable materials
- Moisture, mold, and water resistant

PRODUCT SPECIFICATIONS:

- Each slot size is 0.323" (8.2mm) x length at 5" d radial arch
- 7 rectangular straight radial slots
- Over 9.14 square inches (58.96 square cm) of open vent area

MATERIAL SPECIFICATIONS:

Raw Material: Cement, fibres, quartz sand, nonhazardous fillers

Density: 1.0<D ≤1.2 g/cm3

Asbestos Content: 100% asbestos-free


Fire resistance: non-combustible

Water Absorption: ≤40%

Resistant Bending Strength: ≤10.5 MPa dry

Moisture Movement: 0.25 %

Freeze Thaw: No distortion after 25 repeated cycles of freezing and thawing



For questions or additional information, please contact us at:



info@envisivent.com

