



HUSQVARNA 122HD60

Husqvarna 122HD60 is a low noised and light weight hedge trimmer for domestic use with easy to use functions such as Smart Start® and adjustable rear handle.



LowVib®

Effective anti-vibration dampeners absorb vibration, sparing the user's arms and hands.



Smart Start®

The engine and starter have been designed so the machine starts quickly with minimum effort. Resistance in the starter cord is reduced by up to 40%.

Low noise

The low noise engine technology and the special design make this hedge trimmer quiet and easy to use. Very important for everyone who operates in residential areas.



Multi position handle

The rear handle can be put in multi positions to facilitate cutting the sides and top of hedges.



FEATURES

- Low noise engine technology
- Smart Start® for easy starting
- LowVib® sparing the user's arms and hands
- Multi position handle for easier cutting
- Extended reach with long cutter bar
- Auto return stop switch for easy starting
- Air purge for easier cold starting

Technical Specifications	
CAPACITY	
Clutch engagement speed (±120)	4300 rpm
Cutting speed	4050 cut/min
Idling speed	2800 rpm
Knife adjustment range, up/down Down	0°
Knife adjustment range, up/down Up	0°
Max engine/motor RPM	9000 rpm
Maximum power speed	7800 rpm
Power output	0.6 kW
Teeth opening	28 mm
Torque, max.	0.8 Nm
Torque, max. at rpm	6000 rpm
CERTIFICATIONS	
#Approved according to CE	Yes
Cert machine dir. 2006/42/EC Decl. No.	SEC/10/2280
DIMENSIONS	
Article gross weight	8000 g
Article net weight	6030 g
Knife Length	59 cm
Recommended maximum twig diameter	20 mm
Weight	4.9 kg
Weight (excl. cutting equipment)	4.9 kg
ENGINE	
Carburetor	Ruixing
Cylinder bore	32 mm
Cylinder displacement	21.7 cm ³
Cylinder stroke	27 mm
Electrode gap	0.5 mm
Engine Family CARB	LHVXS.0224EB
Engine Family EPA	LHVXS.0224EB
Gear ratio	4.44
Ignition module air gap	0.3 mm
Max engine/motor RPM	9000 rpm
Spark plug	Husqvarna HQT-4 672201
EQUIPMENT	
Air filter type	Foam
Technical Platform	HPH-A051
Wireless Connectivity	Not applicable
LUBRICANTS	
Fuel consumption	575 g/kWh
Fuel tank volume	0.3 l
Lubricant type	Husqvarna 2 stroke or equiv. at 50:1
Power/fuel type	Gasoline
PACKAGING	
Packaging height	282 mm
Packaging length	1210 mm
Packaging volume	78.5 dm ³
Packaging width	230 mm
Pallet layers	6
Quantity in Master pack	1
EMISSION DATA CARB	
Engine Family EPA	LHVXS.0224EB
Engine Family CARB	LHVXS.0224EB
Exhaust emissions (CO average)	254.87 g/kWh
Exhaust emissions (CO average)	1543 g/kWh
Exhaust emissions (HC average)	42.02 g/kWh
Exhaust emissions (NOx average)	0.46 g/kWh
EMISSION DATA EPA	
Exhaust emissions (CO average)	254.87 g/kWh
Exhaust emissions (CO FEL)	536 g/kWh
Exhaust emissions (CO average)	1543 g/kWh
Exhaust emissions (HC average)	42.02 g/kWh
Exhaust emissions (NOx average)	0.46 g/kWh
EMISSION DATA EU	
Exhaust emissions (CO average)	230.89 g/kWh
Exhaust emissions (CO average)	1528 g/kWh
Exhaust emissions (CO2 EU V)	1528 g/kWh
Exhaust emissions (HC average)	42.55 g/kWh

Technical Specifications

Exhaust emissions (NOx average)	0.37 g/kWh
MATERIALS	
Master pack: Paper + Cardboard	0 g
Metal total	0 g
Other plastic: rigid	64 g
Paper	3800 g
Paper + Cardboard total	3800 g
PE total	0 g
PET total	0 g
Plastic foil	0 g
Plastic rigid	64 g
Plastic total	64 g
PS/EPS/HIPS total	0 g
SOUND AND NOISE	
Sound power level, guaranteed (LWA)	101 dB(A)
Sound power level, measured	100 dB(A)
Sound pressure level at operators ear	94 dB(A)
VIBRATION	
Daily Vibration (Aeqv)	4.1 m/s ²
Daily Vibration Exposure (A8)	2.71 m/s ²
Daily Vibration Time (Time factor)	3.5 h
Equivalent vibration level (ahv, eq) front handle	4.1 m/s ²
Equivalent vibration level (ahv, eq) rear handle	3.6 m/s ²