




HUSQVARNA 125BVx

Efficient hand held blowers that combines high blowing power with user friendliness. Perfect for home owners. Well balanced and easy to manoeuvre thanks to in-lined air out let. Easy to start with Smart Start® technology. Delivered with flat and round nozzle. Vac kit included.



Auto return stop switch

Stop switch automatically resets to the ON position for trouble-free starting.



In lined outlet

The fan housing is designed so that the air stream is in lined with the handle. This makes the machine very easy to manoeuvre.

Mulching function

Mulching knives reduce material and increase bag capacity. 16:1 ratio mulching function.



Cruise control

Fan speed can be set for easier handling.



FEATURES

- Mulching knives increase vac bag capacity
- Easy to operate with in lined air outlet
- Auto return stop switch for easy starting
- Air speed cruise control
- Adjustable tube length
- Air purge for easier cold starting
- Intuitive controls
- Smart Start® for easy starting
- Vac capable to collect debris
- Comfortable handles

Technical Specifications	
CAPACITY	
Air flow in housing	13.31 m ³ /min
Air flow in pipe	12.03 m ³ /min
Air speed	76 m/s
Air speed (flat nozzle)	76 m/s
Air speed (round nozzle)	58.12 m/s
Blow speed	273 km/h
Blowing Force	12.5 N
Idling speed	3000 rpm
Maximum power speed	8000 rpm
Max engine/motor RPM	10000 rpm
Power output	0.8 kW
Vac bag capacity	64.35 l
CERTIFICATIONS	
#Approved according to CE	Yes
Cert machine dir. 2006/42/EC Decl. No.	YES
Commercial Warranty	0
Homeowner Warranty	1 Years
DIMENSIONS	
Article gross weight	8000 g
Article net weight	4000 g
Weight	4.35 kg
ENGINE	
Carburetor	Zama C1Q
Cylinder bore	35 mm
Cylinder displacement	28 cm ³
Cylinder stroke	28.7 mm
Electrode gap	0.6 mm
Fuel tank volume	0.5 l
Fuel consumption	575 g/kWh
Idling speed	3000 rpm
Maximum power speed	8000 rpm
Power output	0.8 kW
Spark plug	Champion RCJ6Y
EQUIPMENT	
OEM Harness	Single harness
OEM Nozzle type	Round+ Flat
OEM Vacuum Kit	Yes
LUBRICANTS	
Fuel consumption	575 g/kWh
Fuel tank volume	0.5 l
Lubricant type	Husqvarna 2 stroke or equiv. at 50:1
Power source	Petrol
Power/fuel type	Gasoline
MATERIALS	
Master pack: Paper + Cardboard	0 g
Metal total	0 g
Paper + Cardboard total	0 g
PE total	0 g
PET total	0 g
Plastic foil	0 g
Plastic rigid	0 g
Plastic total	0 g
PS/EPS/HIPS total	0 g
PACKAGING	
Box Print	4 Color Print (White Box)
Packaging height	480 mm
Packaging length	530 mm
Packaging volume	7.1232 dm ³
Packaging width	280 mm
Pallet layers	2
Quantity in Master pack	1
EMISSION DATA	
Exhaust emissions (CO average)	138 g/kWh
Exhaust emissions (CO average)	168 g/kWh
Exhaust emissions (CO average)	1457 g/kWh
Exhaust emissions (CO2 EU V)	1392 g/kWh

Technical Specifications

Exhaust emissions (HC average)	28 g/kWh
Exhaust emissions (HC average)	41.5 g/kWh
Exhaust emissions (NOx average)	1 g/kWh
Exhaust emissions (NOx average)	0.4 g/kWh
EMISSION DATA EPA	
Exhaust emissions (CO average)	168 g/kWh
Exhaust emissions (HC average)	41.5 g/kWh
Exhaust emissions (NOx average)	0.4 g/kWh
EMISSION DATA EU	
Exhaust emissions (CO average)	138 g/kWh
Exhaust emissions (CO average)	1457 g/kWh
Exhaust emissions (HC average)	28 g/kWh
Exhaust emissions (NOx average)	1 g/kWh
SOUND AND NOISE	
Sound level	112 dB(A)
Sound power level, guaranteed (LWA)	112 dB(A)
Sound power level, measured	109 dB(A)
Sound pressure (15m)	70 dB(A)
Sound pressure level at operators ear	94 dB(A)
VIBRATION	
Equivalent vibration level (ahv, eq) handle	11.1 m/s ²