




HUSQVARNA 129C

Professionals turn to Husqvarna for powerful engines that make tough jobs easy. With Husqvarna Trimmer 129C, that power is available to consumers as well. 129C features a powerful 27cc engine and professional quality – combined with a focus on ease of use. It is easy to start thanks to Smart Start®, intuitive controls and the automatic stop return switch – a feature that automatically resets to the ON position for trouble-free starting. 129C comes with a curved shaft for easy trimming.



Long curved shaft

Extra long curved shaft for extended reach and superior ergonomics.



Auto return stop switch

Stop switch automatically resets to the ON position for trouble-free starting.

Intuitive controls

The choke and purge are easy to reach and understand.



Easier cold starting

Starting a cold engine requires less effort thanks to the air purge.



FEATURES

- Intuitive controls
- Auto return stop switch for easy starting
- Long curved shaft, better control
- Air purge for easier cold starting
- Smart Start® for easy starting
- Transparent fuel tank, easy to check fuel level
- Comfortable handle design

Technical Specifications	
CAPACITY	
Clutch engagement speed (± 120)	4200 rpm
Idling speed	2800 rpm
Maximum power speed	8000 rpm
Maximum rpm output shaft	8500 rpm
Output shaft thread	3/8"-24H
Power output	0.85 kW
CERTIFICATIONS	
#Approved according to CE	Yes
Cert machine dir. 2006/42/EC Decl. No.	Yes
Commercial Warranty	90 Days
Homeowner Warranty	2 Years
DIMENSIONS	
Article gross weight	8165 g
Article net weight	6125 g
Cutting width	43 cm
Tube length	973.13 mm
Tube diameter	25.4 mm
Weight	4.98 kg
Weight (excl. cutting equipment)	4.49 kg
ENGINE	
Cylinder bore	36 mm
Cylinder displacement	27.6 cm ³
Cylinder stroke	27 mm
Electrode gap	0.5 mm
Ignition module air gap	0.3 mm
Spark plug	Husqvarna HQT-4 672201
EQUIPMENT	
Gear ratio	1
OEM Grass blade	--
OEM Harness	--
OEM Saw blade	--
OEM Trimmer head	T25 (R)
Output shaft thread	3/8"-24H
LUBRICANTS	
Fuel consumption	604 g/kWh
Fuel tank volume	0.27 l
Lubricant type (bevel gear)	Mineral grease
Lubricant type	Husqvarna 2 stroke or equiv. at 50:1
PACKAGING	
Box Print	1 Color Print (Brown Box)
Packaging height	286 mm
Packaging length	1565 mm
Packaging volume	120.849 dm ³
Packaging width	270 mm
Pallet layers	4
Quantity in Master pack	1
EMISSION DATA EU	
Exhaust emissions (CO ₂ EU V)	1580 g/kWh
MATERIALS	
Master pack: Paper + Cardboard	0 g
Metal total	0 g
Paper	60000 g
Paper + Cardboard total	60000 g
PE total	0 g
PET total	0 g
Plastic foil	0 g
Plastic rigid	0 g
Plastic total	0 g
PS/EPS/HIPS total	0 g
SOUND AND NOISE	
Sound power level, guaranteed (LWA)	114 dB(A)
Sound power level, measured	106 dB(A)
Sound pressure level at operators ear	93 dB(A)
VIBRATION	
Equivalent vibration level (ahv, eq) left handle	3.7 m/s ²
Equivalent vibration level (ahv, eq) right handle	3.6 m/s ²

