




## HUSQVARNA 129L

Professionals turn to Husqvarna for powerful engines that make tough jobs easy. With Husqvarna Trimmer 129L, that power is available to consumers as well. Trimmer 129L features a powerful 27cc engine and professional quality – combined with a focus on ease of use. It is easy to start thanks to Smart Start®, intuitive controls and the automatic stop return switch – a feature that automatically resets to the ON position for trouble-free starting. 129L comes with a straight shaft for better reach, e.g. under bushes.



### Easier cold starting

Starting a cold engine requires less effort thanks to the air purge.



### Auto return stop switch

Stop switch automatically resets to the ON position for trouble-free starting.

### Intuitive controls

The choke and purge are easy to reach and understand.



### Smart Start®

The engine and starter have been designed so the machine starts quickly with minimum effort. Resistance in the starter cord is reduced by up to 40%.



## FEATURES

- Intuitive controls
- Auto return stop switch for easy starting
- Air purge for easier cold starting
- Smart Start® for easy starting
- Straight shaft for extended reach
- Transparent fuel tank, easy to check fuel level
- Comfortable handle design
- Grass bevel gear for best cutting performance

Technical Specifications	
<b>CAPACITY</b>	
Clutch engagement speed (±120)	4200 rpm
Idling speed	2800 rpm
Maximum power speed	8000 rpm
Maximum rpm output shaft	7200 rpm
Output shaft thread	M10x1.25V
Power output	0.6 kW
<b>CERTIFICATIONS</b>	
#Approved according to CE	Yes
Cert machine dir. 2006/42/EC Decl. No.	Yes
Commercial Warranty	90 Days
Homeowner Warranty	2 Years
<b>DIMENSIONS</b>	
Article gross weight	7390 g
Article net weight	5309 g
Tube length	1174.16 mm
Tube diameter	25.4 mm
Weight	5.37 kg
Weight (excl. cutting equipment)	4.76 kg
<b>ENGINE</b>	
Cylinder bore	36 mm
Cylinder displacement	27.6 cm <sup>3</sup>
Cylinder stroke	27 mm
Electrode gap	0.5 mm
Engine Family CARB	A053
Engine Family EPA	A053
Ignition module air gap	0.3 mm
Spark plug	NGK CMR6A
<b>EQUIPMENT</b>	
Drive gear angle	30°
Gear ratio	19
OEM Grass blade	--
OEM Harness	--
OEM Saw blade	--
OEM Trimmer head	T25 (L)
Output shaft thread	M10x1.25V
<b>LUBRICANTS</b>	
Fuel consumption	604 g/kWh
Fuel tank volume	0.27 l
Lubricant type (bevel gear)	Mineral grease
Lubricant type	Husqvarna 2 stroke or equiv. at 50:1
<b>PACKAGING</b>	
Packaging height	286 mm
Packaging length	1794 mm
Packaging volume	138.533 dm <sup>3</sup>
Packaging width	270 mm
Quantity in Master pack	1
<b>EMISSION DATA CARB</b>	
Engine Family EPA	A053
Engine Family CARB	A053
<b>EMISSION DATA EU</b>	
Exhaust emissions (CO2 EU V)	1580 g/kWh
<b>MATERIALS</b>	
Master pack: Paper + Cardboard	0 g
Metal total	0 g
Paper	60000 g
Paper + Cardboard total	60000 g
PE total	0 g
PET total	0 g
Plastic foil	0 g
Plastic rigid	0 g
Plastic total	0 g
PS/EPS/HIPS total	0 g
<b>SOUND AND NOISE</b>	
Sound power level, guaranteed (LWA)	114 dB(A)
Sound power level, measured	106 dB(A)
Sound pressure level at operators ear	95 dB(A)
<b>VIBRATION</b>	

#### Technical Specifications

Equivalent vibration level (ahv, eq) left handle	9.9 m/s <sup>2</sup>
Equivalent vibration level (ahv, eq) right handle	8.9 m/s <sup>2</sup>