



HUSQVARNA 320iB

Lightweight, easy to use and quiet battery blower. An easy tap on the keypad starts the machine instantly at all times and the cruise control means full focus on blowing leaves and debris away. The blower also has a boost power mode that gives you a little extra power when needed.



Low maintenance

No refilling of fuel, less parts to serve and an electronically controlled drive system means less downtime and low operation costs.



Low noise levels

Low noise levels enable longer working hours and the possibility to work in noise sensitive and restricted areas.

Boost effect

Maximized blowing speed during limited time through easy accessible boost mode.



Excellent ergonomics

Excellent ergonomics through its exceptional product balance, comfortable handle grip and intuitive keypad.



FEATURES

- Maximized blowing speed through easy accessible boost mode.
- Low noise levels enable longer working hours.
- Low maintenance and less downtime
- Superb balance, grip and intuitive keypad gives excellent ergonomics.
- Gear up for nonstop operation
- Cruise controlled blowing speed for optimum handling.
- Low total weight through few components and lightweight motor.
- Ergonomic handle with easy access to the controls.
- Allows you to quickly switch the same battery between different product applications and keep working.
- High torque to weight ratio for increased efficiency and reliability.

Technical Specifications

BATTERY	
Battery	No
Battery runtime (free run) with savE activated	26 min
Battery type	Li-Ion
Battery voltage	36 V
Number of batteries included	--
CAPACITY	
Air flow in housing	12.5 m ³ /min
Air flow in housing	750 m ³ /h
Air flow in pipe	10.8 m ³ /min
Air flow in pipe	648 m ³ /h
Air flow in pipe, boost mode	12.4 m ³ /min
Air flow in pipe, boost mode	744 m ³ /h
Air speed	46 m/s
Air speed, boost mode	54 m/s
Air speed, boost mode (round nozzle)	54 m/s
Air speed (round nozzle)	44 m/s
Blowing Force	9 N
Blowing Force, boost mode	13 N
DIMENSIONS	
Article gross weight	4223 g
Article net weight	2860 g
Tube diameter	69 mm
Tube length	425 mm
Weight without battery	2.4 kg
ENGINE	
Motor type	BLDC (brushless)
LUBRICANTS	
Power source	Battery
Power/fuel type	Battery
MATERIALS	
Master pack: Paper + Cardboard	0 g
Metal total	0 g
Paper + Cardboard total	5365 g
PE total	0 g
PET total	0 g
Plastic foil	0 g
Plastic rigid	0 g
Plastic total	0 g
PS/EPS/HIPS total	0 g
PACKAGING	
Packaging height	645 mm
Packaging length	300 mm
Packaging volume	58.05 dm ³
Packaging width	300 mm
Quantity in Master pack	1
SOUND AND NOISE	
Sound power level, guaranteed (LWA)	96 dB(A)
Sound power level, measured	95 dB(A)
Sound pressure level at operators ear	81 dB(A)
VIBRATION	
Daily Vibration (Aeqv)	0.55 m/s ²
Daily Vibration Exposure (A8)	0.4 m/s ²
Daily Vibration Time (Time factor)	2 h
Equivalent vibration level (ahv, eq) rear handle	0.7 m/s ²