

HUSQVARNA 520iHD70

Powerful yet lightweight and well-balanced battery-powered hedge trimmer for commercial use with 70cm double-sided cutting bar that gives you a great range. New proprietary motor and new powerful battery will allow you to maximise your working time. The pivoting rear handle makes it easier when cutting both vertically and horizontally.



Silent operation

The noise level from our battery machines are up to 13 dB(A) lower than a petrol machine – which is a huge difference. A reduction of 3 dB(A) is usually perceived as a halving of the noise level. This makes work a lot more pleasant for you – and also allows you to work in the most public of settings.



Our battery accessories allow you to carry on and get the job done as quickly and efficiently as possible.



Low maintenance

No refilling of fuel, less parts to serve and an electronically controlled drive system means less downtime and low operation costs.



Multi position handle

The rear handle can be put in multi positions to facilitate cutting the sides and top of hedges.



FEATURES

- Low noise level for a pleasant work environment
- Low maintenance and less downtime
- Gear up for nonstop operation
- Multi position handle for easier cutting
- High power equally to petrol performance
- Allows you to quickly switch the same battery between different product applications and keep working.
- Low total weight through few components and lightweight motor.

- Weatherproof (IPX4) Use in all weather conditions
- The key pad is very easy to operate.
- Well balanced for easy handling
- Smart battery pack position, placed horizontally through the body of the machine.
- Choose savE[™] mode for maximum runtime
- The 4000 cuts per minute ensure great cutting results.

0.4TTPDV	
BATTERY	
Battery	No
DEM Battery charger	
Sattery type	Li-lon
Battery voltage	36 V
lumber of batteries included	
Veight with battery	5.2 kg
CAPACITY	
Cutting speed	4000 cut/min
Feeth opening	32 mm
DIMENSIONS	
article gross weight	6000 g
rticle net weight	4130 g
ínife Length	70 cm
Veight without battery	3.9 kg
ENGINE	· ·
Gear ratio	0.10
Motortype	PMDC (4-brush)
EQUIPMENT	T MEO (T Brush)
	F2CLUD.
echnical Platform	536 LiHD
UBRICANTS	
Power/fuel type	Battery
PACKAGING	
Packaging height	288 mm
Packaging length	636 mm
Packaging volume	54.95 dm³
Packaging width	300 mm
Quantity in Master pack	1
MATERIALS	
faster pack: Paper + Cardboard	0 g
Metal total	0 g
Other plastic: rigid	90 g
Paper	4400 q
Paper + Cardboard total	4400 g
PE total	Og
PET total	0 g
Plastic foil	0 g
Plastic rigid	90 g
Plastic total	90 g
PS/EPS/HIPS total	Og
SOUND AND NOISE	·
ound power level, guaranteed (LWA)	94 dB(A)
ound power level, measured	89 dB(A)
ound pressure level at operators ear	78 dB(A)
IBRATION	7 O (LD(N)
	25 /2
aily Vibration (Aeqv)	3.5 m/s ²
Daily Vibration Exposure (A8)	2.1 m/s² 3 h
Daily Vibration Time (Time factor)	
quivalent vibration level (ahv. eq) front handle quivalent vibration level (ahv. eq) rear handle	2.3 m/s² 3.5 m/s²