




HUSQVARNA 525L

Robust, durable machine built for demanding trimming. Easy to maintain and service.



X-Torq® engine

The X-Torq® engine design reduces harmful exhaust emissions by up to 75% and increases fuel efficiency by up to 20%.



Auto return stop switch

Stop switch automatically resets to the ON position for trouble-free starting.

Intuitive controls

The choke and purge are easy to reach and understand.



Easier cold starting

Removes air from carburetor and fuel system for easy starting.



FEATURES

- Intuitive controls
- Auto return stop switch for easy starting
- X-Torq® engine cuts emission and fuel consumption
- Air purge for easier cold starting
- Smart Start® for easy starting
- Easy to use trimmer head
- Efficient air filter

| Technical Specifications | |
|---|--------------------------------------|
| CAPACITY | |
| Clutch engagement speed (±120) | 4000 rpm |
| Idling speed | 3000 rpm |
| Maximum power speed | 8500 rpm |
| Maximum rpm output shaft | 6500 rpm |
| Power output | 1 kW |
| Torque, max. | 1.2 Nm |
| Torque, max. at rpm | 6000 rpm |
| CERTIFICATIONS | |
| Commercial Warranty | 2 Years |
| Homeowner Warranty | 2 Years |
| DIMENSIONS | |
| Article gross weight | 8369 g |
| Article net weight | 5647 g |
| Cutting width | 46 cm |
| Tube length | 1483 mm |
| Tube diameter | 24 mm |
| Weight (excl. cutting equipment) | 4.4 kg |
| ENGINE | |
| Cylinder bore | 34 mm |
| Cylinder displacement | 25.4 cm ³ |
| Cylinder stroke | 28 mm |
| Electrode gap | 0.65 mm |
| Ignition module air gap | 0.3 mm |
| Spark plug | NGK BPMR8Y |
| EQUIPMENT | |
| Connected digital function set (calc) | FMS : Released 2019-01-01 |
| Drive gear angle | 30 ° |
| Gear ratio | 19 |
| Grass blade | Not included |
| Harness | Not included |
| Saw blade | Not included |
| Trimmer head | T35 M10 |
| LUBRICANTS | |
| Fuel consumption | 600 g/kWh |
| Fuel tank volume | 0.51 l |
| Lubricant type (bevel gear) | Mineral grease |
| Lubricant type | Husqvarna 2 stroke or equiv. at 50:1 |
| PACKAGING | |
| Packaging height | 245 mm |
| Packaging length | 1830 mm |
| Packaging volume | 125.54 dm ³ |
| Packaging width | 280 mm |
| Quantity in Master pack | 1 |
| MATERIALS | |
| Master pack: Paper + Cardboard | 0 g |
| Metal total | 0 g |
| Paper + Cardboard total | 0 g |
| PE total | 0 g |
| PET total | 0 g |
| Plastic foil | 0 g |
| Plastic rigid | 0 g |
| Plastic total | 0 g |
| PS/EPS/HIPS total | 0 g |
| SOUND AND NOISE | |
| Sound power level, guaranteed (LWA) | 107 dB(A) |
| Sound power level, measured | 110 dB(A) |
| Sound pressure level at operators ear | 98 dB(A) |
| VIBRATION | |
| Equivalent vibration level (ahv, eq) left handle | 3 m/s ² |
| Equivalent vibration level (ahv, eq) right handle | 2.8 m/s ² |