



## HUSQVARNA 530iBX

Powered by Husqvarna's powerful BLi backpack battery, the handheld 530iBX blower is low in weight but big on all-weather performance (IPX4). Full of smart features including an intuitive keypad, optimised ergonomics, improved cruise control and boost mode, all designed to maximise uptime and productivity.



### Cruise control

Blowing speed can be set at optionally rpm for optimum handling.



### Advanced motor fan design

Best performance in pro battery class due to the advanced electric motor fan design.

### Li-ion power

The Li-ion battery provides long lasting power and top class performance.

### Boost effect

Maximized blowing speed during limited time through easy accessible boost mode.



## FEATURES

- Li-ion power, long lasting power and top class performance.
- Best performance in class due to the advanced motor fan design.
- Cruise controlled blowing speed for optimum handling.
- Maximized blowing speed through easy accessible boost mode.
- Ergonomic handle with easy access to the controls.
- Low total weight through few components and lightweight motor.
- Weatherproof (IPX4) - Use in all weather conditions
- Superb balance, grip and intuitive keypad gives excellent ergonomics.
- Low noise levels enable longer working hours.
- High torque to weight ratio for increased efficiency and reliability.
- Working with harness and eyelet equipped machine gives a comfortable working position.
- Easy to operate with in lined air outlet
- Low maintenance and less downtime
- Allows you to quickly switch the same battery between different product applications and keep working.
- Gear up for nonstop operation

Technical Specifications	
<b>BATTERY</b>	
Battery	No
OEM Battery charger	--
Battery type	Li-Ion
Battery voltage	36 V
Number of batteries included	--
<b>CAPACITY</b>	
Air flow in pipe	12.4 m <sup>3</sup> /min
Air flow in pipe	744 m <sup>3</sup> /h
Air flow in pipe, boost mode	14.1 m <sup>3</sup> /min
Air flow in pipe, boost mode	846 m <sup>3</sup> /h
Air speed	49.6 m/s
Air speed, boost mode	56.2 m/s
Air speed, boost mode (round nozzle)	56.2 m/s
Air speed (round nozzle)	49.6 m/s
Blowing Force	12 N
Blowing Force, boost mode	16 N
<b>DIMENSIONS</b>	
Article gross weight	1685 g
Article net weight	2329 g
Tube diameter	71.2 mm
Weight without battery	2.9 kg
<b>ENGINE</b>	
Motor type	BLDC (brushless)
<b>LUBRICANTS</b>	
Power source	Battery
Power/fuel type	Battery
<b>MATERIALS</b>	
Master pack: Paper + Cardboard	0 g
Metal total	0 g
Paper + Cardboard total	0 g
PE total	0 g
PET total	0 g
Plastic foil	0 g
Plastic rigid	0 g
Plastic total	0 g
PS/EPS/HIPS total	0 g
<b>PACKAGING</b>	
Packaging height	282 mm
Packaging length	638 mm
Packaging volume	52.18 dm <sup>3</sup>
Packaging width	290 mm
Pallet layers	4
Quantity in Master pack	1
<b>SOUND AND NOISE</b>	
Sound power level, guaranteed (LWA)	91 dB(A)
Sound power level, measured	90 dB(A)
Sound pressure level at operators ear	77.6 dB(A)
<b>VIBRATION</b>	
Daily Vibration (Aeqv)	0.4 m/s <sup>2</sup>
Daily Vibration Exposure (A8)	0.2 m/s <sup>2</sup>
Daily Vibration Time (Time factor)	3 h
Equivalent vibration level (ahv, eq) rear handle	0.4 m/s <sup>2</sup>