



HUSQVARNA 530iPT5

Telescopic battery pole saw for professionals, with 5m telescopic reach and performance that surpasses petrol equivalents. Maximum performance and durability with low weight, excellent ergonomics and quiet operation for use in any location at any time of day.



Battery through body design (Pat.pend.)

Smart battery pack position, placed horizontally through the body of the machine. Reduces the risk of having dirt, chips, dust and water accumulate in the battery compartment, causing connector issues. Also, it means the weight of the battery can be placed in or near the desired center of gravity and in the rotational axis of the product, resulting in increased maneuverability. The through body design also offers a high degree of flexibility since it allows battery packs of different sizes to be used.

savE™

Choose between normal or savE™ mode, depending on conditions, for maximum power or maximum runtime. Either way, you'll always get a perfect result.

Weatherproof (IPX4)

This battery-powered Husqvarna machine fulfils the IPX4 classification for rain resistance. This makes it a long-lasting and reliable tool that can be used all year round in all weather conditions.

Intuitive key pad

The key pad is very easy to operate.



FEATURES

- Weatherproof (IPX4) - Use in all weather conditions
- Choose savE™ mode for maximum runtime
- Smart battery pack position, placed horizontally through the body of the machine.
- The key pad is very easy to operate.
- In-house developed brushless motor provides a high and consistent torque.
- Ergonomic handle with easy access to the controls.
- A harness relieves weight for both arms and shoulders and provides a less strenuous working position.
- Telescopic tube for quick cutting height adjustment
- Fast, smooth cutting
- Rear impact guard
- Low noise level for a pleasant work environment
- Low maintenance and less downtime
- Allows you to quickly switch the same battery between different product applications and keep working.

| Technical Specifications | |
|---|---|
| BATTERY | |
| Battery | No |
| Battery type | Li-Ion |
| Battery voltage | 36 V |
| CAPACITY | |
| Chain speed at max power | 20 m/s |
| DIMENSIONS | |
| Article gross weight | 8000 g |
| Article net weight | 6000 g |
| Bar length | 250 mm |
| Length, extended, including cutting equipment | 400 cm |
| Size | 10" |
| Tube diameter | 24 mm |
| Tube length | 2205 mm |
| Weight (excl. battery and cutting equipment) | 5 kg |
| Weight (excl. cutting equipment) | 5 kg |
| ENGINE | |
| Motor type | BLDC (brushless) |
| EQUIPMENT | |
| Chain type | H00 |
| Connected digital function set (calc) | : Released 2019-01-01No BT Product w HTV : Released 2019-08-28 |
| Pitch | 1/4" |
| Sprocket type | Spur 8 |
| LUBRICANT | |
| Oil tank volume | 0.15 l |
| Power/fuel type | Battery |
| MATERIALS | |
| Master pack: Paper + Cardboard | 0 g |
| Metal total | 0 g |
| Paper | 5 g |
| Paper + Cardboard total | 5 g |
| PE total | 0 g |
| PET total | 0 g |
| Plastic foil | 0 g |
| Plastic rigid | 74 g |
| Plastic total | 74 g |
| PS/EPS/HIPS total | 0 g |
| PACKAGING | |
| Packaging height | 224 mm |
| Packaging length | 2696 mm |
| Packaging volume | 172.72 dm ³ |
| Packaging width | 286 mm |
| Quantity in Master pack | 1 |
| SOUND AND NOISE | |
| Sound power level, guaranteed (LWA) | 98 dB(A) |
| Sound power level, measured | 98 dB(A) |
| Sound pressure level at operators ear | 83 dB(A) |
| VIBRATION | |
| Daily Vibration (Aeqv) | 1.4 m/s ² |
| Daily Vibration Exposure (A8) | 0.4 m/s ² |
| Daily Vibration Time (Time factor) | 0.5 h |
| Equivalent vibration level (ahv, eq), front handle, collapsed | 1.4 m/s ² |
| Equivalent vibration level (ahv, eq) rear handle | 1.2 m/s ² |
| Equivalent vibration level (ahv, eq), rear handle, extended | 1.2 m/s ² |