



HUSQVARNA G5500P

Large sized, powerful and efficient generator for powering homes and work sites in environments where electricity supply may be limited. 5.0kW (50Hz) rated output supplied by a reliable, easy start petrol engine with 25L fuel tank for continuous drive. Ergonomic design and user-friendly dashboard ensure good portability and ease of use even in tough conditions. **Electric start optional - Battery excluded**.



Electric start for effortless starting

Makes the mower very easy to start. Simply turn the key.



External fuel cap for easy refueling

External fuel cap for easy refueling

Visible fuel level

Transparent fuel indicator makes it easy to check fuel level.



Transport handle for convenient lifting and transport

Convenient transport handle facilitates lifting and transport.



FEATURES

- Visible fuel level
- External fuel cap for easy refueling
- Electric start for effortless starting
- Transport handle for easier lifting and transport.

| Technical Specifications | |
|---------------------------------|------------------------|
| CAPACITY | |
| Horsepower | 6.8 hp |
| Power | 5000 W |
| DIMENSIONS | |
| Article gross weight | 91000 g |
| Article net weight | 87000 g |
| Weight | 88 kg |
| EMISSION DATA | |
| Exhaust emissions (CO2 EU V) | 610 g/kWh |
| ENGINE | |
| Cylinder displacement | 389 cm ³ |
| Motor/engine manufacturer | Weima |
| Motor/engine model | Husqvarna Engine |
| EQUIPMENT | |
| Air filter type | Dry |
| Starter | Recoil |
| Technical Platform | Generators EMM |
| LUBRICANTS | |
| Engine oil capacity (L) | 1.1 |
| Engine oil type | SAE 10W-30 |
| Fuel consumption | 395 g/kWh |
| Fuel tank volume (with reserve) | 27 l |
| MATERIALS | |
| Master pack: Paper + Cardboard | 0 g |
| Metal total | 0 g |
| Paper + Cardboard total | 0 g |
| PE total | 0 g |
| PET total | 0 g |
| Plastic foil | 0 g |
| Plastic rigid | 0 g |
| Plastic total | 0 g |
| PS/EPS/HIPS total | 0 g |
| PACKAGING | |
| Packaging height | 715 mm |
| Packaging length | 555 mm |
| Packaging volume | 230.16 dm ³ |
| Packaging width | 580 mm |
| Quantity in Master pack | 1 |