



HUSQVARNA T535i XP®

For professional users who want a lightweight, extremely easy-to-use top handle chainsaw with high performance. Perfect for arborists. A robust chainsaw with excellent ergonomics, high performance and high chainspeed.

Automatic shutdown

The product is automatically shut down after 3 minutes of being idle, which prolongs the life of the battery and also lower the risk for injuries when left unattended. With the chainbrake activated, the shutdown occurs after 30 minutes.

savE™

Choose between normal or savE™ mode, depending on conditions, for maximum power or maximum runtime. Either way, you'll always get a perfect result.

Inertia chain brake

Effective inertia-activated chain brake.



Gear up for nonstop operation

Our battery accessories allow you to carry on and get the job done as quickly and efficiently as possible.



FEATURES

- Increased safety, inertia activated chain brake
- Choose savE™ mode for maximum runtime
- Automatically shut down after 3 minutes of being idle
- Gear up for nonstop operation
- The flip-up tank cap is easy to open.
- The retaining function prevents losing the bar nuts.
- Fast, smooth cutting
- High power equally to petrol performance
- In-house developed brushless motor provides a high and consistent torque.
- Allows you to quickly switch the same battery between different product applications and keep working.
- Rope eyelet in rear handle
- The key pad is very easy to operate.
- Quick connection to the climbing harness

Technical Specifications

BATTERY	
OEM Battery charger	--
OEM Battery	--
Battery type	Li-Ion
Battery voltage	36 V
CAPACITY	
Chain speed at max power	20 m/s
DIMENSIONS	
Article gross weight	4204 g
Article net weight	3313 g
Bar length (inch)	14"
Bar length	350 mm
Weight (excl. battery and cutting equipment)	2.4 kg
ENGINE	
Motor type	BLDC (brushless)
EQUIPMENT	
Bar mount type	Small
Chain type	SP21G
Chainsaw sub-group	Arborists Tree-care chainsaws
Gauge	1.1 mm
Handle type	Standard
Pitch	.325" mini
Sprocket type	Spur 7
LUBRICANT	
Oil pump capacity Max	8 ml/min
Oil pump type	Automatic
Oil tank volume	0.2 l
Power/fuel type	Battery
MATERIALS	
Master pack: Paper + Cardboard	0 g
Metal total	0 g
Paper + Cardboard total	0 g
PE total	0 g
PET total	0 g
Plastic foil	0 g
Plastic rigid	0 g
Plastic total	0 g
PS/EPS/HIPS total	0 g
PACKAGING	
Packaging height	269 mm
Packaging length	472 mm
Packaging volume	31.996 dm ³
Packaging width	252 mm
Quantity in Master pack	1
SOUND AND NOISE	
Sound power level, guaranteed (LWA)	106 dB(A)
Sound power level, measured	104 dB(A)
Sound pressure level at operators ear	93 dB(A)
VIBRATION	
Daily Vibration (Aeqv)	2.5 m/s ²
Daily Vibration Exposure (A8)	1.25 m/s ²
Daily Vibration Time (Time factor)	2 h
Equivalent vibration level (ahv, eq) front handle	2 m/s ²
Equivalent vibration level (ahv, eq) rear handle	2.4 m/s ²