



HUSQVARNA T540i XP®

Husqvarna T540i XP is our most powerful battery-powered top-handle chainsaw, equivalent to a 40cc pro petrol saw when fitted with a BLi200X battery. This saw is the ideal tool for all professional tree care. Designed for arborists who want a smooth, high performance chainsaw. Features excellent ergonomics, high chain speed, low weight and all the benefits of battery power, without compromising cutting performance.



Rope attachment

A sturdy point for fastening a rope, making it easy to hoist the saw up into a tree.



Unobstructed view

The hand guard design allows for an unobstructed view while doing precise cuts.

High chain speed

High chain speed for fast, smooth cutting



Weatherproof (IPX4)

This battery-powered Husqvarna machine fulfils the IPX4 classification for rain resistance. This makes it a long-lasting and reliable tool that can be used all year round in all weather conditions.



FEATURES

- Fast, smooth cutting
- Unobstructed view
- Rope eyelet in rear handle
- Weatherproof (IPX4) - Use in all weather conditions
- Quick connection to the climbing harness
- Automatically shut down after 3 minutes of being idle
- Adjustable chain oil pump
- The key pad is very easy to operate.
- Gear up for nonstop operation
- Allows you to quickly switch the same battery between different product applications and keep working.
- Choose savE™ mode for maximum runtime
- The retaining function prevents losing the bar nuts.
- In-house developed brushless motor provides a high and consistent torque.
- The flip-up tank cap is easy to open.
- Increased safety, inertia activated chain brake

Technical Specifications	
BATTERY	
Battery type	Li-Ion
Battery voltage	36 V
CAPACITY	
Chain speed at max power	24 m/s
DIMENSIONS	
Article gross weight	4105 g
Article net weight	3510 g
Bar length (inch)	14"
Bar length	350 mm
Weight (excl. battery and cutting equipment)	2.5 kg
ENGINE	
Motor type	BLDC (brushless)
EQUIPMENT	
Bar mount type	Small
Chain type	SP21G
Chainsaw sub-group	Arborists Tree-care chainsaws
Gauge	1.1 mm
Pitch	.325" mini
Sprocket type	Spur 7
LUBRICANT	
Oil pump capacity Max	19 ml/min
Oil pump capacity Min	9 ml/min
Oil pump type	Adjustable flow
Oil tank volume	0.2 l
Power/fuel type	Battery
MATERIALS	
Master pack: Paper + Cardboard	0 g
Metal total	0 g
Paper + Cardboard total	0 g
PE total	0 g
PET total	0 g
Plastic foil	0 g
Plastic rigid	0 g
Plastic total	0 g
PS/EPS/HIPS total	0 g
PACKAGING	
Packaging height	258 mm
Packaging length	490 mm
Packaging width	280 mm
Quantity in Master pack	1
SOUND AND NOISE	
Sound power level, guaranteed (LWA)	103 dB(A)
Sound power level, measured	101 dB(A)
Sound pressure level at operators ear	92 dB(A)
VIBRATION	
Daily Vibration (Aeqv)	3.4 m/s ²
Daily Vibration Exposure (A8)	1.9 m/s ²
Daily Vibration Time (Time factor)	2.4 h
Equivalent vibration level (ahv, eq) front handle	2.1 m/s ²
Equivalent vibration level (ahv, eq) rear handle	3.4 m/s ²