

0204 1xN Coupler Array

C9310-S



1x3 1310 nm & 1550 nm Tap Coupler Module, Tap Ratio: TERM, Coupler Ratio: 50/50

The C9310-S is a 1x3 1310 nm & 1550 nm tap coupler module, tap ratio: TERM, coupler ratio: 50/50. This highly reliable coupler module offers very low insertion loss, low polarization dependence and excellent environmental stability. It can be used for optical communication, HFC & fiber sensors, fiber laser, optical amplifier and photonics integration.

FEATURES

- Low Excess Loss
- Low Insertion Loss
- Low PDL
- High Stability and Reliability

USE IN

- Optical Communication
- Local Area Network
- FTTH & LAN
- HFC & Fiber Sensors

Operating Wavelength	1310 nm & 1550 nm	
Dimensions	111.125x50.8x12.7 mm	
Port Configuration	1x3	
Fiber Type	Corning SM-28e with 900 µm Loose Tube	
Connectors	SC/APC (Output Port), None (Input Port & Tap Port)	
Operating Temperature	-45°C to 80°C	

Wavelength Tested	1310 nm		1550 nm				
	Input 1	Output 1	Output 2	O	Output 1	Output 2	O
Insertion Loss		-3.18 dB	-2.85 dB		-3.21 dB	-2.81 dB	
Loss Variation at Output Ports		0.33 dB			0.40 dB		
Excess Loss		0.19 dB			0.22 dB		

