

## 0204 1xN Coupler Array

C9505-S



### 1x5 1310 nm & 1550 nm Tap Coupler Module, Tap Ratio: 50/50, Coupler Ratio: 50/50

The C9505-S is a 1x5 1310 nm & 1550 nm tap coupler module, tap ratio: 50/50, coupler ratio: 50/50. This highly reliable coupler module offers very low insertion loss, low polarization dependence and excellent environmental stability.

#### FEATURES

- Low Excess Loss
- Low Insertion Loss
- Low PDL
- High Stability and Reliability

#### USE IN

- Optical Communication
- Local Area Network
- FTTH & LAN
- HFC & Fiber Sensors

Operating Wavelength	1310 nm & 1550 nm
Dimensions	111.26x50.99x12.71 mm
Port Configuration	1x5
Fiber Type	Corning SM-28e with 900 μm Loose Tube
Connectors	SC/APC (Output Port), None (Input & Tap Port)
Operating Temperature	-45°C to 80°C

#### Wavelength Tested: 1310 nm

Input 1	Output 1	Output 2	Output 3	Output 4	Tap
Insertion Loss	9.40 dB	9.14 dB	9.19 dB	9.34 dB	3.22 dB
Loss Variation at Output Ports	0.26 dB				
Excess Loss	0.22 dB				

#### Wavelength Tested: 1550 nm

Input 1	Output 1	Output 2	Output 3	Output 4	Tap
Insertion Loss	9.30 dB	9.45 dB	9.43 dB	9.41 dB	3.22 dB
Loss Variation at Output Ports	0.15 dB				
Excess Loss	0.29 dB				