

0903 1064 nm (1+N)*1 Combiner (HP)

HB2001



980/1060(1+2)x1 Combiner, Backward Pump, Fiber Type: Nufern PLMA-GDF-10/125-M

The combiner offers high transfer efficiency, air-clad technology for robust power delivery, stable and reliable and custom configurations available. It can be used for high power component and fiber amplifier.


FEATURES

- High Transfer Efficiency
- Air-Clad Technology for Robust
- Stable and Reliable
- Custom Configurations Available
- Power Delivery

USE IN

- High Power Component
- Fiber Amplifier

MECHANICAL DRAWING



Port Configuration	(1+2)x1		
Pump Wavelength	980 nm		
Signal Wavelength	1060 nm		
Signal Input Fiber	X/125	X/250	20/400
Pump Fiber	105/125 0.22 NA or 200/220 0.22 NA		
Signal Output Fiber	Y/125 or Y/250	Y/250	20/400
Pump Efficiency	90% min.	93% min.	95% min.
Signal Insertion Loss	0.5 dB max.		
Total Handling Power	50 W	100 W	200 W
Polarization Extinction Ratio	18 dB min. (PM Fiber Type)		
Return Loss	45 dB min.		
Operating Temperature	-5°C to +70°C		
Storage Temperature	-40°C to +85°C		
Dimension	80x14x10 mm		
Fiber Type	Nufern PLMA-GDF-10/125-M		

Order notes to our customers: The default parameters are as follows. For special needs, please contact sales.

1) Connector FC/APC, 900 um, 1 m by default for all devices except for high power devices.

2) Slow axis working, fast axis blocked, connector key is aligned to slow axis by default for PM devices.