

0101 Isolator

L6000-S



C-band Polarization Insensitive Optical Isolator, Dual Stage, SM

The L6000-S is a C-band polarization insensitive isolator, dual stage, SM. The device is characterized with high isolation, high return loss and low insertion loss. It has been widely used in fiberoptic amplifiers, fiberoptic systems testing, fiberoptic LAN systems and other fiberoptic communication equipments to suppress back reflection and back scattering.


FEATURES

- High Isolation
- Low Insertion Loss
- High Return Loss
- Low Polarization Sensitivity

USE IN

- Fiber Optic Amplifiers
- Fiber Optic Systems Testing
- Fiber Optic LAN Systems
- Telecommunications

MECHANICAL DRAWING



Operating Wavelength	1525 nm to 1570 nm
Isolation	56 dB typ.; 45 dB min.
Insertion Loss	0.5 dB typ.; 0.7 dB max.
Return Loss (In/Out)	65/60 dB min.
PDL	0.05 dB max.
Polarization Mode Dispersion	0.05 ps
Bandwidth	±30 nm
Power Handling	300 mW
Fiber Type	SM Fiber
Dimension	5.5x5.5x35 mm
Operating Temperature	-10°C to +75°C
Storage Temperature	-40°C to +85°C

Order notes to our customers: The default parameters are as follows. For special needs, please contact sales.

1) Connector FC/APC, 900 um, 1 m by default for all devices except for high power devices.

2) Slow axis working, fast axis blocked, connector key is aligned to slow axis by default for PM devices.