


1003 Pulse Laser Diode

LD-1310P-DL



1310 nm Pulse Laser Diode, InGaAs Strained, 150 mW Peak Power

The LD-1310P-DL is a high-power pulse laser diode that has been designed as a light laser source for pulsed fiber lasers. It can be used for Optical Time Domain Reflectometer (OTDR) and other pulse application. It feature high peak power and excellent reliability. Housed inside a dual Inline package, LD-1310P-DL is extremely compact. Contact Optilab for more information.

FEATURES

- Wavelength Range: 1310±10 nm
- Built in Isolator
- Multi-Mode Fabry Perot
- High Peak Output Power 100 mW @ 400 mA

USE IN

- LiDAR
- Remote Sensing
- OTDR
- Optical Spectroscopy

Wavelength Range	1310±10 nm
Peak Optical Output Power	100 mW typ. @ 1% Duty Cycle
Drive Current	400 mA @ 100 mW
Forward Voltage	2.5 V typ.
Threshold Current	20 mA typ.
Rise Time	1 ns typ. (Highly Depends on Driving Circuit)
Fall Time	1 ns typ. (Highly Depends on Driving Circuit)
Operating Temperature	-20°C to +60°C
Storage Temperature	-40°C to +70°C
Operating Humidity	95% @30°C max.
Optical Fiber Type	SMF
Optical Connector	FC/APC, Others Available
Pulsed Forward Current	600 mA
Reverse Voltage	2 V
Cooler Current	1.3 A
Cooler Voltage	3.5 V