

1402 PM Patchcord

P2200-P



1550 nm PM Patchcord, 900 μm Buffer

The device is a 1550 nm, 900 μm buffer PM patchcord. It offers very low insertion loss, high return loss, high extinction ratio, high stability and reliability. It can be used for optical fiber amplifiers, test instrument, fiber sensor, research and fiber laser.

FEATURES

- Low Insertion Loss
- High Return Loss
- High Stability and Reliability
- High Extinction Ratio

USE IN

- Optical Fiber Amplifiers
- Test Instrument
- Research
- Fiber Laser
- Fiber Sensor

Center Wavelengths	1550 nm
Insertion Loss	0.5 dB max.
Extinction Ratio	23 dB min.
Return Loss	60 dB min.
Fiber Type	PM Panda Fiber
Key Orientation	Slow Axis
Tolerance for Axis Alignment	±3 deg
Diameter	900 μm Buffer
Operating Temperature	-20°C to +70°C
Storage Temperature	-40°C to +85°C

ORDERING OPTION

P2200-P-L-Connector #1-Connector #2

L length : 1 m, 2 m, 3 m, 4 m, 5 m, 6 m, 7 m, 8 m, 9 m, 10 m..... , +\$15 for each additional meter

Connector #1 : customized, FCA, FCU etc.

Connector #2 : customized, FCA, FCU etc.

Order notes to our customers: The default parameters are as follows. For special needs, please contact sales.

1) Connector FC/APC, 900 um, 1 m by default for all devices except for high power devices.