

1402 PM Patchcord

P2201-P



1550 nm PM Patchcord, 3 mm Buffer

The device is 1550 nm, 3 mm buffer PM patchcord. It offers very low insertion loss, high return loss, high extinction ratio, high stability and reliability. It can be used for optical fiber amplifiers, test instrument, fiber sensor, research and fiber laser.

FEATURES

- Low Insertion Loss
- High Return Loss
- High Stability and Reliability
- High Extinction Ratio

USE IN

- Optical Fiber Amplifiers
- Test Instrument
- Research
- Fiber Laser
- Fiber Sensor

| | |
|------------------------------|----------------|
| Center Wavelengths | 1550 nm |
| Insertion Loss | 0.5 dB max. |
| Extinction Ratio | 23 dB min. |
| Return Loss | 60 dB min. |
| Fiber Type | PM Panda Fiber |
| Key Orientation | Slow Axis |
| Tolerance for Axis Alignment | ±3 deg |
| Diameter | 3 mm Buffer |
| Operating Temperature | -20°C to +70°C |
| Storage Temperature | -40°C to +85°C |

ORDERING OPTION

P2201-P-L-Connector #1-Connector #2

L length : 1 m, 2 m, 3 m, 4 m, 5 m, 6 m, 7 m, 8 m, 9 m, 10 m..... , +\$20 for each additional meter

Connector #1 : customized, FCA, FCU etc.

Connector #2 : customized, FCA, FCU etc.

Order notes to our customers: The default parameters are as follows. For special needs, please contact sales.

1) Connector FC/APC, 900 um, 1 m by default for all devices except for high power devices.