

ART.107.527.2

CERTIFICATIONS

- NFPA 1936:2015 COMPLIANT
- ISO 9001:2008

GENESIS

RESCUE SYSTEMS
WWW.GENESISRESCUE.COM

EFORCE 2.0 21/36 RAM

MILWAUKEE TOOLS 28V 5AH BATTERY

Can provide up to 30 minutes of continuous operation.

VARIABLE CONTROL SWITCH

To the left - Closes
To the right - Opens

ON/OFF SWITCH

Pushing switch puts the tool into idle mode and will run in idle mode for 30 seconds unless variable control is used.

LED LIGHTS

Will illuminate for the entire duration of the operation of the tool.

REMOVABLE HEADS

Both rear and forward facing heads are removable. Simply unscrew the traditional heads and screw on V-heads. Ensure that the replacement heads are completely screwed in.



CHARGING

Milwaukee's 5AH 28 volt battery can be fully charged in 1.5 hours.

SPECIFICATIONS

LENGTH CLOSED(IN/MM) - 21.3/542

WIDTH(IN/MM) - 5.3/134

DEPTH(IN/MM) - 12.8/325

WEIGHT(LBS/KGS) - 34.6/15.7

POWER SOURCE - 28V MILWAUKEE TOOLS

OPERATING PRESSURE(PESI/BAR) - 10,000/700

LENGTH EXTENDED(IN/MM) - 35.8/910

STROKE(IN/MM) - 14.6/370

MAX PUSHING FORCE(LBF/KN) - 25,021/111.3

NFPA 1936 COMPLIANT - YES

[CLICK TO WATCH
ANGLED V-HEAD
INSTALL VIDEO](#)

[CLICK TO WATCH
ANGLED V-HEAD
TIPS & TRICKS VIDEO](#)

GENESIS IS
TRAINING
FOLLOW US

