ART.107.202.6

CERTIFICATIONS

- NFPA 1936:2015 COMPLIANT
- ISO 9001:2008



EFORCE 2.0 C165 CUTTER

ON/OFF SWITCH

Pushing switch puts the tool into idle mode and will run in idle mode for 30 seconds unless variable control is used.

LED LIGHTS

Will illuminate for the entire duration of the operation of the tool.

CHARGING Milwaukee's 5AH 28 volt battery can be fully

charged in 1.5 hours.

VERSION PCT.3.2016

VARIABLE CONTROL SWITCH

MILWAUKEE TOOLS

28V 5AH BATTERY

Can provide up to 30

minutes of continuous

operation.

To the left - Closes To the right - Opens

D-HANDLE

Allows user to operate the tool from any angle. Loosen the star knob to allow the handle to rotate 360 degrees.

SPECIFICATIONS

LENGTH(IN/MM) - 33.3/845

WIDTH(IN/MM) - 9.3/236

DEPTH(IN/MM) - 8.5/217

WEIGHT(LBS/KGS) - 43/19.5

POWER SOURCE - 28V MILWAUKEE TOOLS

OPERATING PRESSURE(PSI/BAR) - 10,000/700

OPENING(IN/MM) - 5.9/150

MAX CUTTING FORCE(LBF/KN) - 144,450/642

NFPA 1936 COMPLIANT - YES

NFPA 1936 LEVEL RATING - A8 | B5 | C6 | D7 | E9

FORGED BLADES

The forging process produces greater consistency, quality, and hardness.



