

ART.107.526.2

GENESIS

RESCUE SYSTEMS
WWW.GENESISRESCUE.COM

EFORCE 2.0 NXTGEN C236 CUTTER

MILWAUKEE TOOLS 28V 5AH BATTERY

Can provide up to 30 minutes of continuous operation.

VARIABLE CONTROL SWITCH

To the left - Closes
To the right - Opens

D-HANDLE

Allows user to operate the tool from any angle. Loosen the star knob to allow the handle to rotate 360 degrees.

ON/OFF SWITCH

Pushing switch puts the tool into idle mode and will run in idle mode for 30 seconds unless variable control is used.

LED LIGHTS

Will illuminate for the entire duration of the operation of the tool.



CHARGING

Milwaukee's 5AH 28 volt battery can be fully charged in 1.5 hours.

SPECIFICATIONS

LENGTH(IN/MM) - 38.7/982

WIDTH(IN/MM) - 10.2/260

DEPTH(IN/MM) - 9.4/241

WEIGHT(LBS/KGS) - 51.8/23.5

POWER SOURCE - 28V MILWAUKEE TOOLS

OPERATING PRESSURE(Psi/BAR) - 10,000/700

OPENING(IN/MM) - 7.9/200

MAX CUTTING FORCE(LBF/KN) - 236,000/1050

NFPA 1936 COMPLIANT - YES

NFPA 1936 LEVEL RATING - A8 | B9 | C8 | D9 | E9

NXTGEN INSERTS

Inserts can be purchased and installed by the end user. Inserts are engineered to cut UHSS and Boron.

NXTGEN INSERTS

Holes in the blade reduce weight and increase strength.

[CLICK TO WATCH
NXTGEN BLADE
CHANGE VIDEO](#)

GENESIS IS
TRAINING
FOLLOW US

