

EFORCE

THE NEXT GENERATION OF EXTRICATION



GENESIS
RESCUE SYSTEMS

SVTTM
SMART VALVE TECHNOLOGY

SSSTM
SMART SWAP SYSTEM

THE NEXT GENERATION OF UNTETHERED EXTRICATION

EFORCE

UNDER THE HOOD

The next generation of untethered extrication. We started the redesign with the drive unit, adding a smaller more efficient brushless motor that makes even more power than eForce 2.0. Encased it within a state of the art housing equipped with more LEDs and impact resistant polymer. We ALSO packed in two new state of the art technologies SSS™ and SVT™.

THE POWER

Get durability, runtime, and power to complete the toughest extrications. The M28 Lithium-Ion Battery Pack is built to handle high-torque applications. Managed by Milwaukee's exclusive REDLINK Intelligence, the battery features overload protection to prevent you from damaging your cordless power tools in heavy-duty situations, while the discharge protection prevents cell damage. The temperature management system and individual cell monitoring help maximize battery life.



All controls are indicated by distinctive red color for easy location and use.

Rear Facing LED lighting illuminates the working area.

SVT™

Higher speed thanks to a new, even more efficient drive system. Smart Valve Technology (SVT) senses pressure variations to ensure maximum tool performance.

360° rotating and folding handle made from glass fiber reinforced plastic helps minimize storage space requirements.

This also protects the operator from electric shock up to 1,000 Volts.

SSS™

The Smart Swap System allows EFORCE battery tools to be converted to conventional hydraulic tools and vice versa.

NEW SMART SWAP SYSTEM ALLOWS MORE FLEXIBILITY

Genesis Rescue's new generation of hose-bound cutters, spreaders and combi tools can be converted to EFORCE battery-powered devices and vice versa at any time via a new Smart Swap System. This means more flexible decision-making. The conversion can only be done by a Genesis certified service technician.


Tools can be converted in a few steps:



MORE SPEED THROUGH SMART VALVE TECHNOLOGY

Smart valve technology senses pressure variations that are needed to complete the task.

EFORCE rescue tools start in the volume stage and transition into the pressure stage. The volume stage makes tools move quickly and the pressure stage is where all critical "WORK" of extrication is performed. This is where Smart Valve Technology out performs the competition. The SVT returns EFORCE tools to the volume stage instantly, allowing faster tool response and drastically decreasing rescue times.



EFORCE



Lifetime Warranty

C195-SL3 NXTGEN

Part Number: ART.109.351.2



Length (mm/in)	898	35.4
Width (mm/in)	236	9.3
Height (mm/in)	241	9.5
Weight (kg/lbs) w/battery	20.6	45.4
Cutting Opening (mm/in)	185	7.3
Ingress Protection Rating	IP54	IP54
NFPA Cut Rating	A8-B9-C7-D9-E9-F4	A8-B9-C7-D9-E9-F4
Nominal Pressure (bar/psi)	700	10,000

EFORCE



Lifetime Warranty

C236-SL3 NXTGEN

Part Number: ART.109.351.4



Length (mm/in)	994	39.1
Width (mm/in)	260	10.2
Height (mm/in)	241	9.5
Weight (kg/lbs) w/battery	23.5	51.8
Cutting Opening (mm/in)	210	8.3
Ingress Protection Rating	IP54	IP54
NFPA Cut Rating	A8-B9-C8-D9-E9-F4	A8-B9-C8-D9-E9-F4
Nominal Pressure (bar/psi)	700	10,000

EFORCE



Lifetime Warranty

C236-SL3 EFORCE
Part Number: ART.109.351.4S



Length (mm/in)	982	38.7
Width (mm/in)	260	10.2
Height (mm/in)	241	9.5
Weight (kg/lbs) w/battery	23.5	51.8
Cutting Opening (mm/in)	210	8.3
Ingress Protection Rating	IP54	IP54
NFPA Cut Rating	A8-B9-C8-D9-E9-F4	A8-B9-C8-D9-E9-F4
Nominal Pressure (bar/psi)	700	10,000

EFORCE



Lifetime Warranty

All-9 EFORCE
Part Number: ART.109.351.0



Length (mm/in)	1029	40.5
Width (mm/in)	298	11.7
Height (mm/in)	241	9.5
Weight (kg/lbs) w/battery	26.3	58.0
Cutting Opening (mm/in)	265	10.4
Ingress Protection Rating	IP54	IP54
NFPA Cut Rating	A9-B9-C9-D9-E9-F5	A9-B9-C9-D9-E9-F5
Nominal Pressure (bar/psi)	700	10,000

Images and Specifications are subject to change without notice



Lifetime Warranty

Genesis Advantage:

Energy Efficient
Lightest EFORCE cutter available

Voltage: 28V
Amp Hours: 5 Ah
Watt Hours: 140 Wh

Warranty: Lifetime

C165-SL3 EFORCE
Part Number: ART.109.856.5

Length (mm/in)	878	34.6
Width (mm/in)	236	9.3
Height (mm/in)	241	9.5
Weight (kg/lbs) w/battery	20.1	44.3
Cutting Opening (mm/in)	165	6.5
Ingress Protection Rating	IP54	IP54
NFPA Cut Rating	A8-B5-C6-D6-E8-F3	A8-B5-C6-D6-E8-F3
Nominal Pressure (bar/psi)	700	10,000



Compatible Systems:

SVT
SST
Extrication Backpack
Genesis 28v 5Ah Battery
EPACK 15 Ah
110v Tether Adapter



 Lifetime Warranty

Genesis Advantage:
Energy Efficient
Best cost to power ratio

Voltage: 28V
Amp Hours: 5 Ah
Watt Hours: 140 Wh

Warranty: Lifetime

C365-SL3 EFORCE
Part Number: ART.109.636.3

Length (mm/in)	981	38.6
Width (mm/in)	298	11.7
Height (mm/in)	241	9.5
Weight (kg/lbs) w/battery	25.8	56.9
Cutting Opening (mm/in)	170	6.7
Ingress Protection Rating	IP54	IP54
NFPA Cut Rating	A8-B9-C8-D9-E9-F5	A8-B9-C8-D9-E9-F5
Nominal Pressure (bar/psi)	700	10,000

Compatible Systems:
SVT
SST
Extrication Backpack
Genesis 28v 5Ah Battery
EPACK 15 Ah
110v Tether Adapter

Images and Specifications are subject to change without notice

EFORCE



Lifetime Warranty

11C-SL3 EFORCE Part Number: ART.109.351.5



Length (mm/in)	811	31.9
Width (mm/in)	192	7.6
Height (mm/in)	241	9.5
Weight (kg/lbs) w/battery	13.6	30.0
Cutting Opening (mm/in)	221	8.7
Spreading Width (mm/in)	270	10.6
Pulling Distance (mm/in)	352	13.9
Ingress Protection Rating	IP54	IP54
Highest Spreading Force (kN/lbf)	32	7,200
Lowest Spreading Force (kN/lbf)	24	5,400
Highest Pulling Force (kN/lbf)	45	10,125
Lowest Pulling Force (kN/lbf)	34	7,650
NFPA Cut Rating	A6-B7-C6-D7-E7-F3	A6-B7-C6-D7-E7-F3
Nominal Pressure (bar/psi)	700	10,000

EFORCE



Lifetime Warranty

14C-SL3 EFORCE Part Number: ART.109.664.7



Length (mm/in)	927	36.5
Width (mm/in)	236	9.3
Height (mm/in)	241	9.5
Weight (kg/lbs) w/battery	18.1	39.9
Cutting Opening (mm/in)	285	11.2
Spreading Width (mm/in)	360	14.2
Pulling Distance (mm/in)	380	15.0
Ingress Protection Rating	IP54	IP54
Highest Spreading Force (kN/lbf)	40	9,000
Lowest Spreading Force (kN/lbf)	28	6,300
Highest Pulling Force (kN/lbf)	56	12,600
Lowest Pulling Force (kN/lbf)	39	8,775
NFPA Cut Rating	A7-B8-C7-D9-E8-F5	A7-B8-C7-D9-E8-F5
Nominal Pressure (bar/psi)	700	10,000

EFORCE



Lifetime Warranty

15C-SL3 EFORCE

Part Number: ART.109.664.9



Length (mm/in)	933	36.7
Width (mm/in)	236	9.3
Height (mm/in)	241	9.5
Weight (kg/lbs) w/battery	19.2	42.3
Cutting Opening (mm/in)	295	11.6
Spreading Width (mm/in)	370	14.6
Pulling Distance (mm/in)	360	14.2
Ingress Protection Rating	IP54	IP54
Highest Spreading Force (kN/lbf)	39	8,775
Lowest Spreading Force (kN/lbf)	28	6,300
Highest Pulling Force (kN/lbf)	54	12,150
Lowest Pulling Force (kN/lbf)	39	8,775
NFPA Cut Rating	A7-B8-C7-D8-E8-F5	A7-B8-C7-D8-E8-F5
Nominal Pressure (bar/psi)	700	10,000

EFORCE



Lifetime Warranty

17C-SL3 EFORCE

Part Number: ART.109.261.1



Length (mm/in)	969	38.1
Width (mm/in)	236	9.3
Height (mm/in)	241	9.5
Weight (kg/lbs)	21	46.3
Cutting Opening (mm/in)	342	13.5
Spreading Width (mm/in)	405	15.9
Pulling Distance (mm/in)	406	16.0
Ingress Protection Rating	IP54	IP54
Highest Spreading Force (kN/lbf)	40	9,000
Lowest Spreading Force (kN/lbf)	29	6,525
Highest Pulling Force (kN/lbf)	57	12,825
Lowest Pulling Force (kN/lbf)	36	8,100
NFPA Cut Rating	A7-B9-C7-D9-E9-F6	A7-B9-C7-D9-E9-F6
Nominal Pressure (bar/psi)	700	10,000

Images and Specifications are subject to change without notice

EFORCE



Lifetime Warranty

11C-RIT3 EFORCE

Part Number: ART.109.337.7



Length (mm/in)	824	32.4
Width (mm/in)	192	7.6
Height (mm/in)	241	9.5
Weight (kg/lbs) w/battery	14.9	32.8
Cutting Opening (mm/in)	215	8.5
Spreading Width (mm/in)	285	11.2
Pulling Distance (mm/in)	276	10.9
Ingress Protection Rating	IP54	IP54
Highest Spreading Force (kN/lbf)	30	6,750
Lowest Spreading Force (kN/lbf)	26	5,850
Highest Pulling Force (kN/lbf)	41	9,225
Lowest Pulling Force (kN/lbf)	35	7,875
NFPA Cut Rating	A6-B7-C6-D7-E7-F3	A6-B7-C6-D7-E7-F3
Nominal Pressure (bar/psi)	700	10,000

EFORCE



Lifetime Warranty

S44-SL3 EFORCE

Part Number: ART.109.370.3



Length (mm/in)	877	34.5
Width (mm/in)	239	9.4
Height (mm/in)	241	9.5
Weight (kg/lbs)	17.3	38.1
Spreading Width (mm/in)	610	24.0
Pulling Distance (mm/in)	388	15.3
Ingress Protection Rating	IP54	IP54
Highest Spreading Force (kN/lbf)	52	11,700
Lowest Spreading Force (kN/lbf)	41	9,225
Highest Pulling Force (kN/lbf)	42	9,450
Lowest Pulling Force (kN/lbf)	21	4,725
Nominal Pressure (bar/psi)	700	10,000

EFORCE



Lifetime Warranty

S49-SL3 EFORCE
Part Number: ART.109.173.6



Length (mm/in)	982	38.7
Width (mm/in)	282	11.1
Height (mm/in)	241	9.5
Weight (kg/lbs)	20.7	45.6
Spreading Width (mm/in)	735	28.9
Pulling Distance (mm/in)	558	22.0
Ingress Protection Rating	IP54	IP54
Highest Spreading Force (kN/lbf)	76	17,100
Lowest Spreading Force (kN/lbf)	51	11,475
Highest Pulling Force (kN/lbf)	54	12,150
Lowest Pulling Force (kN/lbf)	30	6,750
Nominal Pressure (bar/psi)	700	10,000

EFORCE



Lifetime Warranty

S54-SL3 EFORCE
Part Number: ART.109.173.5



Length (mm/in)	1015	40.0
Width (mm/in)	282	11.1
Height (mm/in)	241	9.5
Weight (kg/lbs)	20.9	46.1
Spreading Width (mm/in)	805	31.7
Pulling Distance (mm/in)	618	24.3
Ingress Protection Rating	IP54	IP54
Highest Spreading Force (kN/lbf)	68	15,300
Lowest Spreading Force (kN/lbf)	46	10,350
Highest Pulling Force (kN/lbf)	52	11,700
Lowest Pulling Force (kN/lbf)	26	5,850
Nominal Pressure (bar/psi)	700	10,000

Images and Specifications are subject to change without notice

EFORCE



Lifetime Warranty

31" Ram EFORCE

Part Number: ART.031.901.2



Length (mm/in) length closed	553	21.8
Width (mm/in)	142	5.6
Height (mm/in)	347	13.7
Weight (kg/lbs) with battery	18.2	40.1
Stroke (mm/in)	287	11.3
Length Extended (mm/in)	840	33.1
Ingress Protection Rating	IP54	IP54
Pulling Force (kN/lbf)	47	10,575
Spreading Force (kN/lbf)	142	31,950
Nominal Pressure (bar/psi)	700	10,000

EFORCE



Lifetime Warranty

41" Ram EFORCE

Part Number: ART.041.901.2



Length (mm/in) length closed	653	25.7
Width (mm/in)	142	5.6
Height (mm/in)	380	15.0
Weight (kg/lbs) with battery	21.6	47.6
Stroke (mm/in)	408	16.1
Length Extended (mm/in)	1061	41.8
Ingress Protection Rating	IP54	IP54
Pulling Force (kN/lbf)	46	10,350
Spreading Force (kN/lbf)	138	31,050
Nominal Pressure (bar/psi)	700	10,000

EFORCE



Lifetime Warranty

21-36 Ram EFORCE
Part Number: ART.107.527.2



Length (mm/in) length closed	542	21.3
Width (mm/in)	134	5.3
Height (mm/in)	325	12.8
Weight (kg/lbs) with battery	15.7	34.6
Stroke (mm/in)	370	14.6
Length Extended (mm/in)	910	35.8
Ingress Protection Rating	IP54	IP54
Spreading Force (kN/lbf)	111.3	25,043
Nominal Pressure (bar/psi)	700	10,150

EFORCE



Lifetime Warranty

22-54 Ram EFORCE
Part Number: ART.107.834.2



Length (mm/in) length closed	586	23.1
Width (mm/in)	134	5.3
Height (mm/in)	349	13.7
Weight (kg/lbs) with battery	20.1	44.3
Stroke Stage 1 (mm/in)	428	16.9
Stroke Stage 2 (mm/in)	372	14.6
Length Extended (mm/in)	1386	54.6
Ingress Protection Rating	IP54	IP54
Force Stage 1 (kN/lbf)	108	24,300
Force Stage 2 (kN/lbf)	62	13,950
Nominal Pressure (bar/psi)	550	7,975

Images and Specifications are subject to change without notice



28V Milwaukee Battery

Part Number: ART.105.375.5

Length (mm/in)	84	3.3
Width (mm/in)	81	3.2
Height (mm/in)	134	5.3
Weight (kg/lbs)	1	2.3

Compatible Systems:
All EFORCE tools
ETORCH

Voltage: 28V
Amp Hours: 5 Ah
Watt Hours: 140 Wh

Warranty: 3 year



28V EPACK 15AH

Part Number: ART.110.100.0Y

Length (mm/in)	258	10.2
Width (mm/in)	195	7.7
Height (mm/in)	112	4.4
Weight (kg/lbs)	5	10.9

Compatible Systems:
All EFORCE tools
ETORCH

Cord Length (mm/in): 4572 / 180

Voltage: 28V
Amp Hours: 15 Ah
Watt Hours: 388 Wh

Warranty: 2 year



28V GENESIS BATTERY

Part Number: ART.107.289.3

Length (mm/in)	83.8	3.3
Width (mm/in)	81.3	3.2
Height (mm/in)	134.6	5.3
Weight (kg/lbs)	1.5	3.2

Compatible Systems:
All EFORCE tools
ETORCH

Voltage: 28V
Amp Hours: 5 Ah
Watt Hours: 140 Wh

Warranty: 3 year



1-BAY CHARGER
Part Number: ART.105.410.9

Length (mm/in)	304	12
Width (mm/in)	222	8.75
Height (mm/in)	127	5

Compatible Systems:

5 Ah Milwaukee 28v battery
 3 Ah Milwaukee 28v battery
 28v Genesis Battery

Warranty: 5 years



3-BAY CHARGER
Part Number: ART.105.410.9

Length (mm/in)	464	18.3
Width (mm/in)	241	9.5
Height (mm/in)	144	5.6
Weight (kg/lbs)	5.3	11.7

Compatible Systems:

5 Ah Milwaukee 28v battery
 3 Ah Milwaukee 28v battery
 28v Genesis Battery

Warranty: 5 years



TETHERING ADAPTER
Part Number: ART.105.410.9

Cord Length (mm/in)	3,657	144
Voltage / Hertz	120V	50-60 Hz
Amps / Watts	8	920
Weight (kg/lbs)	5	11

Compatible Systems:

The tethering adapter is compatible all the tools in the Genesis EFORCE line of tools. EPACK

Warranty: 2 years

Images and Specifications are subject to change without notice



ETORCH LED LIGHT

Part Number: ART.550.100.0

Length with battery (mm/in)	241	9.5
Width (mm/in)	101	4
Height (mm/in)	147	5.8
Weight (kg/lbs)	2.3	5

Compatible Systems:
 Milwaukee 28V 5Ah Battery
 Milwaukee 28V 3 Ah Battery
 28V Genesis Battery
 EPACK

Voltage: 28V

Warranty: Lifetime



ANGLE V-HEAD

THREADED: ART.011.130.2
SLIP FIT: ART.011.130.4

Length (mm/in)	95	3.8
Width (mm/in)	75	2.9
Height (mm/in)	75	2.9
Weight (kg/lbs)	268	5

Compatible Systems:

Threaded & Slip Fit:
 21/36 EFORCE Ram
 31 Inch Push-Pull Ram
 41 Inch Push-Pull Ram

Slip Fit (Ram base only):
 22/54 EFORCE Telescopic Ram

Warranty: Lifetime



EFORCE RAM KIT

Part Number: ART.011.520.5

Length (mm/in)	381	15
Width (mm/in)	114	4.5
Height (mm/in)	267	10.5
Weight (kg/lbs)	4.8	10.6

Compatible Systems:
 21/36 EFORCE Ram
EFORCE Ram Kit Contents:

Angle V-head (Threaded)
 Angle V-head (Slip Fit)
 1 Extension (Multiple options)
 O-Ring Kit

Fits your choice of extension:
 7 inch | 10 inch | 12 inch

Warranty: Lifetime



7" Ram Extensions
Part Number: ART.105.410.9

Length (mm/in)	175	6.9
Weight (kg/lbs)	2	4.4

Compatible Systems:

- 21/36 EFORCE Ram
- 22/54 EFORCE Telescopic Ram

Advantage:

Forged construction, secure lock pin

Warranty: Lifetime



10" Ram Extension
Part Number: ART.383.857.9

Length (mm/in)	250	9.8
Weight (kg/lbs)	2.6	5.7

Compatible Systems:

- 21/36 EFORCE Ram
- 22/54 EFORCE Telescopic Ram

Advantage:

Forged construction, secure lock pin

Warranty: Lifetime



12" Ram Extension
Part Number: ART.106.244.2

Length (mm/in)	320	12.6
Weight (kg/lbs)	3	6.6

Compatible Systems:

- 21/36 EFORCE Ram
- 22/54 EFORCE Telescopic Ram

Advantage:

Forged construction, secure lock pin

Warranty: Lifetime

Images and Specifications are subject to change without notice



RIT Tip

Part Number: ART.109.685.9

Length (mm/in)	124.5	4.9
Width (mm/in)	89	3.5
Height (mm/in)	50.8	2
Weight Per Tip (kg/lbs)	0.9	2.2


Compatible Tools:

11C-RIT3
15C-SL3
17C-SL3

Advantage:

The RIT tip was designed with breaching in mind offering a large surface area for maximum bite.

Warranty: Lifetime



Brute Tip

Part Number: ART.386.732.3

Length (mm/in)	129.5	5.1
Width (mm/in)	43.2	1.7
Height (mm/in)	58.4	2.3
Weight Per Tip (kg/lbs)	0.8	1.75


Compatible Tools:

11C-RIT3
15C-SL3
17C-SL3

Advantage:

Genesis' strongest tip for brute force operation like spreading, peeling, and moving steel.

Warranty: Lifetime



Tip Extension

Part Number: ART.105.189.6

Length (mm/in)	182.9	7.2
Width (mm/in)	35.6	1.4
Height (mm/in)	61	2.4
Weight Per Tip (kg/lbs)	1.2	2.55

Compatible Tools:

11C-RIT3
15C-SL3
17C-SL3

Advantage:

This mid range tip extension offers our users a little more throw as the situation requires.

Warranty: Lifetime



Deluxe Slip Fit Kit
Part Number: ART.011.520.1

Angled V-Head - 1	Spanner Wrench - 1
X-Head - 1	Pulling Shackles and Pins
10 inch Extension - 1	Pulling Adapters
6 Inch Extension - 1	3 Inch Slip Fit Extension

Compatible Tools:
 31 Inch Push-Pull Ram
 41 Inch Push-Pull Ram

Advantage:
 With use of the patented Genesis V-Head there is no need for additional equipment when performing dash related evolutions.

Warranty: Lifetime



Mechanical Ram
Part Number: ART.105.647.8

Min-Max Length (mm/in)	308-650	21.1-25.6
Width (mm/in)	68	2.7
Weight (kg/lbs)	6	13.2

Compatible Tools:
 11C-SL3
 14C-SL3

Advantage:
 A combination tool now has the ability to be a true multi-tool. Cut, Spread, and now a pushing ram.

Warranty: Lifetime



EXTRICATION BACKPACK
Part Number: ART.EXTBP

Length (mm/in)	864	34
Width (mm/in)	304	12
Height (mm/in)	165	6.5
Weight (kg/lbs)	2.6	5.8

Compatible Tools:
 The extrication backpack will fit all the tools in the Genesis EFORCE line of tools.

Advantage:
 A collaboration with one of the worlds largest FD's this pack is designed with tactical rescue in mind. Comfort, Durability and functionality.

Warranty: 3 year

Images and Specifications are subject to change without notice



Lifetime Warranty

Kodiak Deluxe Kit


Part Number: ART.500.102.2

Length (mm/in)	686 27 - (Strut)	864 34 - (Kit)
Width (mm/in)	203 8 - (Strut)	381 15 - (Kit)
Height (mm/in)	203 8 - (Strut)	254 10 - (Kit)
Weight (kg/lbs)	4.8 10.5 - (Strut)	32.7 72 - (Kit)

Kodiak Deluxe Kit Contents

Quantity

15 Inch Extension	2
30 Inch Extension	2
Kodiak Strut with D-ring	2
Ratchet Straps with J-Hook	4
Kodiak Head	2
Carrying Bag	1



Load Limits Per Extension Length



Kodiak Lifting Device
Part Number: ART.500.600.KLD

Length Closed Length Open (mm/in)	775 1130	30.5 44.5
Width (mm/in)	200	8
Depth (mm/in)	4	10
Weight (kg/lbs)	15.5	7

Compatible Tools:

- Standard Kodiak Kit
- Kodiak Deluxe Kit
- Kodiak Tri-Strut Kit

Lifting Capacity - 5,000 lbs | 2,267 kg

Warranty: Lifetime



Standard Kodiak Kit
Part Number: ART.500.100.1

Length (mm/in)	686 27 - (Strut)	864 34 - (Kit)
Width (mm/in)	203 8 - (Strut)	381 15 - (Kit)
Height (mm/in)	203 8 - (Strut)	254 10 - (Kit)
Weight (kg/lbs)	4.8 10.5 - (Strut)	26.3 58 - (Kit)

Standard Kodiak Kit Contents:

- 15 Inch Extension - Qty 2
- 30 Inch Extension - Qty 2
- Kodiak w/Ratchet - Qty 2
- J-Hook - Qty 2
- Kodiak Head - Qty 2
- Carry Bag - Qty 2

Warranty: Lifetime



Kodiak Tri-Strut Kit
Part Number: ART.500.103.3

Length (mm/in)	686 27 - (Strut)	864 34 - (Kit)
Width (mm/in)	203 8 - (Strut)	381 15 - (Kit)
Height (mm/in)	203 8 - (Strut)	254 10 - (Kit)
Weight (kg/lbs)	4.8 10.5 - (Strut)	45.8 101 - (Kit)

Kodiak Tri-Strut Kit Contents:

- 15 Inch Extension - Qty 3
- 30 Inch Extension - Qty 3
- Kodiak w/D-Hook - Qty 3
- Ratchet Straps - Qty 6
- J-Hook - Qty 6
- Kodiak Head - Qty 3
- Carry Bag - Qty 2

Warranty: Lifetime

Images and Specifications are subject to change without notice

EFORCE

THE NEXT GENERATION OF EXTRICATION

**SUBMIT YOUR PHOTOS TO
INFO@GENESISRESCUE.COM**



Photo credit: Box 120 Fire Photography

GENESIS AT WORK

Photo credit: Box 120 Fire Photography



Photo credit: Box 120 Fire Photography



Photo credit: Box 120 Fire Photography





GENESIS
RESCUE SYSTEMS

Genesis Rescue Systems
2780 Culver Ave.
Kettering, Ohio 45429
info@genesisrescue.com
www.genesisrescue.com

RESCUE SYSTEMS