

# FIREBULL®

## F3 Fluorine Free Foam

### FIREBULL A/B



FIREBULL® is manufactured by EnforcerOne, LLC.  
Contact EnforcerOne for more details at  
678-788-8413 or info@enforcerone.com  
www.enforcerone.com

#### PRODUCT INFO:

FIREBULL F3 Fluorine Free Foam is a seamless transition from AFFF products for fire departments. FIREBULL A/B is our newest development in fluorine free firefighting concentrates. FIREBULL A/B is closest in physical characteristics to traditional A/B products but contain NO fluorine or intentionally added PFAS. FIREBULL A/B is low viscosity, mixes easily with water, and is compatible with Class A and B tanks, pumps, and standard firefighting equipment. FIREBULL A/B is applicable from 0.25% for Class A fires to 3% for Class B fire extinguishment and is NFPA 18 compliant.

#### APPLICATIONS

Wetting Agent Class A  
US/European Class A Fires  
Wood, Grass, Coal, Tires, Hay, Cotton,  
Cardboard, Initial Knockdown: 0.25%

Wetting Agent: Class B  
0.25%-1.0%. Reapply as needed.

Cars, Trucks, Heavy Equipment:  
0.50% up to 1.0%

US Class B, European Class B/C Fires  
Non-Polar Solvents:  
Gasoline, Gasoline w/10% Ethanol,  
Jet A, JP4/5/8, Crude Oil, Diesel, Etc.  
3% using .1 GPM/Sq.Ft. Indirect  
Application  
3% using .16 GPM/Sq.Ft. Direct  
Application

Polar Solvents  
Ethanol, Gasoline w/85% Ethanol,  
6% using .3 GPM/Sq.Ft. for 20-30  
minutes. Reapply as needed.

US/European Class D fires/EV fires  
Recommended application is 3% or  
6% using proper equipment.



#### PHYSICAL PROPERTIES

Appearance: Clear Liquid  
PH: 7.0-9.0  
Viscosity: 20 cps  
Density, g/ml: 1.018  
Expansion Ratio: 7.5  
25% Drain Time: 3:26  
Acid Content: None  
Fluorine Content: (TOF) <1ppm  
Min Storage Temp: 35°F (2°C)  
Max Storage Temp: 120°F (49°C)  
Effect of Freeze/Thaw: None

#### CERTIFICATIONS

GreenScreen Certified™ Silver  
UL Rated Class A 0.25%  
UL Rated Class B 0.25%-3%



## Associated Products

PART NUMBER  
FB-AB-005

GreenScreen Certified™ is a registered trademark of Clean Production Action.



FIREBULL  
CLASS A WETTING AGENT



FIREBULL  
TRAINING FOAM



ENFORCER 30 CAFS



ENFORCER 10 CAFS