


Class A Wetting Agent



PRODUCT INFO:

Environmentally formulated FIREBULL Class A Foam is the newest generation in nonfluorinated foam. FIREBULL Class A Foam contains ZERO hazardous materials in the formulation; it will not clog, gum, or corrode foam systems and equipment. This environmentally formulated concentrate implements a dramatically changed chemistry compared to most foams. This chemistry enables FIREBULL Class A Foam to be used in all types of foam portioning systems, compressed air foam systems (CAFS), in-line eductors, and standard foam equipment.

APPLICATIONS

Grass fires and Initial Structural Knockdown: 0.10% - 0.25% Tire Fires, Landfill Fires, Coal Fires and Wildland Fires: 0.25% - 0.50% Car/Vehicle Fires and Overhaul: 0.50% - 1.0%

APPLICATION NOTES

 \bigoplus

Recommended to set foam system defaults between 0.25% and no more than 0.50% Compressed Air Foam Systems (CAFS) should be calibrated using a foaming solution under 50 cps for accurate calibration

FLUSHING INSTRUCTIONS

It is recommended to flush all Class A foam tanks if possible. If not, use as much of previous Class A foam, then add FIREBULL concentrate. Mixing with most Class A foams will not cause harm to systems.

SHELF LIFE

FIREBULL Class A foam has an unlimited shelf-life.

COMPATIBILITY

Compatible with other brands of foam as finished foam. Compatible with other FIREBULL products as a concentrate.

PHYSICAL PROPERTIES

Appearance: Natural Amber PH: 7.5-8.5 Viscosity: 900 cps Min. Storage Temp: 35°F (2°C) Max. Storage Temp: 120°F (-49°C)

Effect of Freeze/Thaw: None

Associated Products



FIREBULL FLUORINE FREE FOAM



FIREBULL TRAINING FOAM



ENFORCER 30 CAFS



ENFORCER 10 CAFS



FIREBULL

FLUORINE FREE FOAMS









FIREBULL F3	FIREBULL CLASS A	FIREBULL TRAINING FOAM	FIREBULL F3 CLIMATE CONTROL
Synthetic Fluorine Free	Fluorine Free Wetting Agent	Fluorine Free Training Foam	Synthetic Fluorine Free Foam Premix
NO PFAS, PFOA, PFOS	Application rates .01% - 1%	Application Training 1%, 3%, 6%	No PFAS, PFOA, PFOS
UL 162 3 %	NO PFAS	NO PFAS	No Dilution Required
PH Neutral	Water Soluble	Water Soluble	Freeze Protected to -40°C
No Hazardous Materials	No Hazardous Materials	No Hazardous Materials	No Hazardous Materials
Vapor Barrier	Non Corrosive, P/H Neutral	Non Corrosive, P/H Neutral	Non Corrosive, P/H Neutral
20-Year Shelf Life	20-Year Shelf Life	20-Year Shelf Life	20-Year Shelf Life
5 gal pail, 55 gal drum, totes	5 gal pail, 55 gal drum, totes	5 gal pail, 55 gal drum, totes	5 gal pail, 55 gal drum, totes



(







VAPORADE PLUS	DUSTADE	FLAMEADE	DOWNPOUR
Explosive Vapor Suppression	Dust Suppression	Flame Retardant	Quenching Agent
Effective on H2S, benzene, hydrocarbons	Control Dust for Longer Periods of Time	Non Boric Acid Alternative	Welding, Mobile Service, Fabrication
Suppresses vapors in tanks and pipelines	Dirt Tracks, Mining, Agriculture	Movie Industry, Set Design, Interiors	Rapidly Cools Hot Metal Surfaces
Water Soluble	Cool Ash, Saw Dust, Combustible Dust	Apply and Dry. Does Not Stain	No Sticky Residue, Evaporates Clean
No Hazardous Materials	Non Corrosive, P/H Neutral	Non Corrosive, P/H Neutral	Non Corrosive, P/H Neutral
Non Corrosive, P/H Neutral	20-Year Shelf Life	20-Year Shelf Life	20-Year Shelf Life
20-Year Shelf Life	5 gal pail, 55 gal drum, totes	5 gal pail, 55 gal drum, totes	32 oz, 5 gal pail, 55 gal drum, totes

ENFORCERONE, LLC. 473 Dividend Dr, Peachtree City, GA 30269 | P: 678.788.8413 F: 678.604.0107 | ENFORCERONE.com