

Approved for Zone 0 gas and Zone 20 dust atmospheres.
 Increased output with added features, the ATEX rated Survivor X right-angle torch is available as a fully rechargeable system or an economical alkaline model that provides a 25% cost savings on batteries.



Strong spring-loaded clip securely grabs onto belts and gear; D-ring provides forward hanging orientation



New charger design:

- Survivor X securely locks into the charger - fits snugly in place
- Quick release latch for one-handed grab-and-go
- Easy to remove with gloved hands



Rubber dome push-button switch easy to use with gloves
 Features battery life indicator

Battery life indicator in switch:
 – Green indicates full charge
 – Turns red when battery is nearing low voltage
 – Flashes red continuously when 15 minutes left of battery life

Unbreakable polycarbonate lens with silicone anti-scratch coating
 Specialized optic combines low profile with strong performance and a wide beam

Rugged nylon polymer body is virtually indestructible



<p>High, low and emergency flash modes:</p> <ul style="list-style-type: none"> – High for a super-bright, smoke piercing beam: 250 lumens; 447m beam distance; runs 3.75 hours (Li-Ion); runs 5 hours (alkaline) – Low for longer run time: 60 lumens; 237m beam distance; runs 15 hours (Li-Ion); runs 15 hours (alkaline) – Flash for signaling: runs 8 hours <p>Optimized electronics provide regulated intensity</p>
<p>IP67 rated; dust-tight and waterproof to 1m for 30 minutes; 2m impact resistance tested</p>
<p>Uses rechargeable lithium ion battery (charges in 5 hours) or three alkaline batteries</p>

<p>PENDING: ATEX: II 1G Ex ia op is IIC T3/T4 Ga; II 1D Ex ia op is IIIC T135° Da IECEX: Ex ia op is IIC T3/T4 Ga; Ex ia op is IIIC T135° Da CE/UKCA: Meets applicable European Community Directives Flashlight meets 500°F requirements of NFPA 1971-8.6 (2013) Charger meets requirements of NFPA 1901-14.1.10.2 (2016) mounted in any position</p>
<p>17.92 cm; Li-ion: 346g; Alkaline: 363g</p>
<p>Limited Lifetime Warranty Visit streamlight.com for full warranty information</p>
<p>#90970 - Survivor X ATEX - Alkaline - Orange #90971 - Survivor X ATEX - Light Only - Orange #90972 - Survivor X ATEX - 100V AC/12V DC - Orange #90973 - Survivor X ATEX - 230V AC/12V DC - Orange #90974 - Survivor X ATEX - 240V AC/12V DC - Orange</p>