



Bottom Mount Refrigerators & Freezers (R290)

Installation, Operation, and Maintenance Instructions

● SPECIFICATIONS

PRODUCT		Solid Full Door Freezer			Solid Full Door Refrigerator		
MODEL		ARF-23	ARF-49	ARF-72	ARR-23	ARR-49	ARR-72
Capacity		650 ℓ (23ft ³)	1,385 ℓ (49ft ³)	2,035 ℓ (72ft ³)	650 ℓ (23ft ³)	1,385 ℓ (49ft ³)	2,035 ℓ (72ft ³)
Exterior Dimensions (including Casters, Door handles)	(W)	695mm (27.4")	1,400mm (55.2")	1,980mm (78.0")	695mm (27.4")	1,400mm (55.2")	1,980mm (78.0")
	(D)	838mm (33")			838mm (33")		
	(H)	2,127 mm (83.7")			2,127 mm (83.7")		
Swing Doors		1	2	3	1	2	3
Shelves		4	8	12	4	8	12
Compressor		3/5HP	3/4HP	1HP	3/8HP	3/8HP	3/8HP
Power Voltage		115V / 60Hz					
Plug In-Installation		NEMA 5-15P		NEMA 14-20P	NEMA 5-15P		
Amps		8.0A	10.5A	14.5A	7.5A	7.5A	7.5A
Range of Temperature		Below -18°C (0°F)			0°C ~ 4°C (+32°F ~ +40°F)		
Refrigerant		R-290					
		100g (3.5 oz)	130g (4.6oz)	140g (4.9oz)	70g (2.5 oz)	90g (3.2oz)	120g (4.2 oz)
Product Weight		124kg (273 lb)	194kg (428 lb)	255kg (562lb)	121kg (267 lb)	186kg (410 lb)	253kg (558lb)