

Rotary Gas-Fired Oven Standard - ST FGR110 Morello Forni




properties; minimum 6" from top to bottom requiring 3" clearance to combustible materials.


- INTELTOUCH-MF10 Touch Screen Electronic Control System.
- Independent intuitive digital safety controls.
- Programmable time, speed, temperature and flame control system.
- Optimized performance and large productivity.
- Emergency Stop push button.
- 220/60/1

DATE:


Rotary Gas-Fired Oven Standard - ST FGR110







Rotary Gas-Fired Oven Standard - ST FGR110 Morello Forni



FLUE CONNECTION

FLUE CONNECTION All ovens are provided with an exhaust flue collar ½" or 2½" in height and 8" or 10" nominal diameter depending on model. The flue collar (ØH) is located on oven top to provide a secure connection to the chimney. The oven flue collar is designed to be connected to chimney listed to UL-103HT. When working on gas only ovens, the oven is suitable for connection to Type B Gas Vent when used with the draft hood. When burning wood, an independent Flue evacuation system is required.

ELECTRICAL CONNECTION

Verify the power supply has the same rating as the oven.

AIR SUPPLY

These ovens require make-up air to replace combustion air and excess air taken out by the flue. Always check for adequate openings to allow required make-up air flow in. Check table included in operations manual.

Model/	FGR110	Cooking Time			
Specifications	(43)				
Power	220/60/1	Capacity	(7) x 11″		
Gas Fitting (inches)	3⁄4	Individual Pizza	2 ~ 3 minutes		
BTU	BTU 136,000				
510	150,000		4 ~ 6 minutes		
Weight (lbs.)	4,200	Pan Pizza			

Model/ Dimensior (inches)	A	В	с	D	E	F	ØН	I	L	Μ	N	0
FGR-110 (43)	65.5	70	40.5	12	37	76.5	10	45.5	32.5	48	10	21.5



Rosito Bisani Imports, Inc. 940 South La Brea Avenue, Los Angeles CA, 90036 Tel: 323-937-1888 • Fax: 323-938-0728 • Toll Free: 1-800-848-4444 E-mail: sales@rosito-bisani.com www.rosito-bisani.com

LISTED

GAS-FIRED

530 South Henderson Road, Suite F, King of Prussia PA, 19406 Tel: 610-265-5950 • Fax: 888-576-8524

Rosito and Bisani Imports reserve the right to make changes in design specifications and/or to make additional improvements in it's products without imposing any obligations upon itself to install them on products previously manufactured. © 2013.