


Project:	
Location:	
Item #:	Quantity:
Model #:	

MODEL: IRT-MPG1980

Granite Top Pizza Prep Tables



ICT-VIP1980B1/3GLASSTOP



- Sanitation. The interior cabinet is built with rounded corners (extensive radius for easy cleaning). Quick ability to take off shelves and slides for interior cleaning. Each cabinet has a drain at the bottom of the unit. When cleaning the unit make sure the drain hose is routed to a floor drain.
 - Doors. Self-closing door system with permanent pressure. Stay open feature included when door remains open after 95 degrees. All doors include triple chamber door gaskets, easy to remove and snap in. Doors are field reversible.
 - Control systems. Higher precision in managing temperature settings. Greater ability to adjust temperature ranges as per the end user's requirement.
- 100% Tested. All condenser units are tested 100%, in helium chambers to refrigerant leak detections.
 - Certified. Audited and Certified by INTERTEK for compliance with UL 471 and NSF 7. AENOR audited and certified by internationally recognized firm. ISO 9001:2008 (Quality); ISO 14001:2004 (Environmental); OSHAS 18001:2007 (Prevention and Worker Safety)

MODEL	Dimensions (inches) (mm)			Nº	Nº Shelves	Ref.	Ref. Weight	Temp. Range	Capacity (Cu. Ft.)	Cond. Unit.	Case Amps	Crated Weight
	W	D	Н	Doors	/Pans		(Lbs.) (gr.)	(°F) (°C)	(L)	H.P.	115 V.	(Lbs.) (Kg.)
IRT-MPG1980			32-3/4	3	3/8	R134a	0.62	33°F/38°F	16.2	1/4	6.5	
	78	27-1/2	830				260	0°C/3°C	460			626 262
	1980	700	55-3/8				0.48	38°F/41°F	1.83	1/6	1.82	
			1417				220	3°C/5°C	35			

ETL LISTED TO UL471 STANDARD AND SANITATION CLASSIFIED TO NSF7 - WE RESERVE THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT PRIOR NOTICE











Infrico USA Corp. 7042 N.W. 46th Street Miami, FL 33166 1.305.777.9599 Office

1.305.777.9598 Fax

www.infrico.us service@infrico.com sales@infrico.com

APPROVALS: AVAILABLE AT:



Project:		
Location:		_
Item #:	Quantity:	
Model #:		

MODEL: IRT-MPG1980

Granite Top Pizza Prep Tables

STANDARD FEATURES

Exterior

- Granite worktop,
- AISI 304 Stainless Steel.

Interior

- AISI 304 Stainless Steel,
- Internal drain plug for easy cleaning,
- Sealed interior floors and rounded cabinet corners.

Insulation

- CFC-Free polyurethane insulation, entire cabinet structure is foamed-in place using a high density polyurethane insulation,
- Low GWP & Zero ODP effect.

> Doors

- Polyurethane insulated doors,
- Self closing doors with stay open feature,
- Stainless Steel heavy-duty hinges,
- Triple chamber snap in door gaskets for easy removal and cleaning,
- Field reversible doors,
- Door locks.
- Door opening: 14-3/4"x20-5/8" (375x526 mm).

Casters

- 4" diameter casters,
- Locks provided on front set.

OPTIONAL FEATURES

- ✓ Set of 6" legs, height adjustable from 5" to 8".
- Stainless Steel wire shelves,
- Additional slide kits,
- Electrical connection is: 220-230 V / 1ph / 50 Hz (plug type varies).

Salad Top

- IRT-VIP1980B1/3GLASSTOP included.
- Top includes 1/3 size polycarbonate food pans, (8) pans.

Shelving

- (1) Plastic coated wire shelves per section,
- Set of Stainless Steel shelf brackets,
- Easy remove for cleaning,
- Dimensions WxD: 12-51/64"x20-7/8" (325x530 mm).
- Compatible with 12"x20" (305x508 mm).sheet pans.

Refrigeration

Digital temperature controller with automatic defrost

- Stainless steel evaporative pan,
- Front-breathing refrigeration system,
- Extractable condensing unit for easy service,
- Evaporator coil coated with anti-corrosion material 100% Polyester,
- Refrigeration system independent for table and counter-top ingredients,
- Refrigeration capacity: 1348 Btu/h (14°F) / 395 W (-10°C).

Electrical

Cord and NEMA 5-15P plug,



- Electrical connection is 115V / 1ph / 60 Hz.
- ETL Listed to UL471 Standard and Sanitation classified to NSF7.

PLAN VIEW

RIGHT VIEW PLAN VIEW ELEVATION 27%" [700.0

ETL LISTED TO UL471 STANDARD AND SANITATION CLASSIFIED TO NSF7 - WE RESERVE THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT PRIOR NOTICE









Infrico USA Corp. 7042 N.W. 46th Street Miami, FL 33166 1.305.777.9599 Office

1.305.777.9598 Fax

www.infrico.us service@infrico.com sales@infrico.com

APPROVALS: AVAILABLE AT:





