

Project:	
Location:	
Item #:	Quantity:
Model #:	

MODEL: ICT-VIP1330B1/3SOLIDLID

COUNTER TOP:

Refrigerated ingredient displays - Solid lid

Important: Do only introduce refrigerated products! For daily cleaning, remove products and disconnect unit.





General Strengths

- Sanitation. The interior cabinet is built with rounded corners (extensive radius for easy cleaning). Quick ability to take off shelves and slides for interior cleaning. Each cabinet has a drain at the bottom of the unit. When cleaning the unit make sure the drain hose is routed to a floor drain.
- Control systems. Higher precision in managing temperature settings. Greater ability to adjust temperature ranges as per the end user's requirement.
- 100% Tested. All condenser units are tested 100%, in helium chambers to refrigerant leak detections.
- Certified. Audited and Certified by INTERTEK for compliance with UL 471 and NSF 7. AENOR audited and certified by internationally recognized firm. ISO 9001:2008 (Quality); ISO 14001:2004 (Environmental); OSHAS 18001:2007 (Prevention and Worker Safety)

MODEL		Dimensions (inches) (mm)			Nº Pans	Ref.	Ref. Weight	Temp. Range	Capacity (Cu. Ft.)	Cond. Unit.	Case Amps	Crated Weight
	W	D	Н	Lid			(Lbs.) (gr.)	(°F) (°C)	(L)	H.P.	115 V.	(Lbs.) (Kg.)
ICT-VIP1330	52-3/8	16-1/4	10-1/4	1 4	4	R134a	0.48	39°F/41°F	1.30	1/6	1.82	108
B1/3solidlid	1328	413	260		-		220	4ºC/6ºC	37			50

Infrico USA Corp.

7042 N.W. 46th Street

Miami, FL 33166

1.305.777.9599 Office 1.305.777.9598 Fax

ETL LISTED TO UL471 STANDARD AND SANITATION CLASSIFIED TO NSF7 - WE RESERVE THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT PRIOR NOTICE











www.infrico.us service@infrico.com sales@infrico.com

APPROVALS: AVAILABLE AT:



Project:		
Location:		_
Item #:	Quantity:	
Model #:		

MODEL: ICT-VIP1330B1/3SOLIDLID

COUNTER TOP:

Refrigerated ingredient displays - Solid lid

STANDARD FEATURES

Exterior

- AISI 304 Stainless Steel.
- AISI 304 Stainless Steel lid,
- Levelling feet.

> Interior

- AISI 304 Stainless Steel,
- Sealed interior floors and rounded cabinet corners,
- Stainless steel 6" deep pans, included.

OPTIONAL FEATURES

✓ Electrical connection is 220-230 V / 1ph / 50 Hz (plug type varies).

Insulation

- CFC-Free polyurethane insulation, entire cabinet structure is foamed-in place using a high density polyurethane insulation,
- Low GWP & Zero ODP effect.

Refrigeration

- Digital temperature controller with automatic defrost
- Cold wall refrigeration system,
- Refrigeration capacity: 973 Btu/h (14°F) / 190 W (-10°C).


Electrical

Cord and NEMA 5-15P plug.




- Electrical connection is 115V / 1ph / 60 Hz
- ETL Listed to UL471 Standard and Sanitation classified to NSF7.

PLAN VIEW




ELEVATION

RIGHT VIEW



PLAN VIEW



ETL LISTED TO UL471 STANDARD AND SANITATION CLASSIFIED TO NSF7 - WE RESERVE THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT PRIOR NOTICE









Infrico USA Corp. 7042 N.W. 46th Street Miami, FL 33166 1.305.777.9599 Office 1.305.777.9598 Fax

www.infrico.us service@infrico.com sales@infrico.com

APPROVALS: AVAILABLE AT:



