

Trim Selection



HEAVY DUTY STAINLESS STEEL CLUTCH LEVER ESCUTCHEON (High Frequency Abusive Situation such as Schools, Hospitals, Industrial / Institutional)

CONSTRUCTION

- Clutch mechanism
- Double heavy duty spring support to prevent sagging and enhance operation
- Grade 1, thru-bolted design. Non-handed design.
- All Stainless Steel heavy duty tailpiece.
Available for fire and non-fire rated rim and vertical rod exit devices
- Standard 6-Pin Schlage "C" Mortise Cylinder included

DOOR THICKNESS


Standard 1 3/4" to 2".

For 2" or 2 1/2" thick door use additional Part # TAIL9

ESCUTCHEON DIMENSIONS

2 5/8" width x 10 5/8" length. Lever length: 4 5/8".

Fits and covers 2 1/8" 161 cutout



Lever Trim Designs



HDESC-00 or

• ICHDESC-00

• ICSDHDESC-00

HDTSESC-00

• ICHDTSESC-00

• ICSDHDTSESC-00

ENTRANCE

Clutch Entrance, key locks or unlocks escutcheon trim.

ANSI Function (08)

Operates as classroom function

HDESC-05 or

• ICHDESC-05

• ICSDHDESC-05

HDTSESC-05

• ICHDTSESC-05

• ICSDHDTSESC-05

STOREROOM

Clutch Storeroom, key unlocks lever, lever retracts latch bolt, otherwise always locked. ANSI Function (09)

HDESC-30

PASSAGE

HDTSESC-30

Trim always operable and free

ANSI Function (14)

HDESC-40

DUMMY

HDTSESC-40

Dummy Escutcheon trim

ANSI Function (02)

TO ORDER RL lever design, add "RL" after "HD" when ordering.

e.g. HDRLESC-00 for HDESC-00 with RL design.

KEYWAY: 6-Pin solid brass "C" keyway Mortise Cylinder standard. Optional: Schlage E, Schlage C-K, Russwin D1-2-3-4, Corbin 59/60, Sargent LA-LB-LC, Falcon/Weiser E, Arrow A, Yale 8, Yale GA and Kwikset. Can also accept Medeco, Assa, Kaba and Cal-Royal HSK High Security Cylinders.

• (IC) **INTERCHANGEABLE CORE:** Interchangeable Core locks will accept compatible 6 or 7-Pin cores with BEST, FALCON and ARROW

• (ICSC) **INTERCHANGEABLE CORE:** Indicates function available with Schlage Full Size Format Interchangeable Core. Corbin, Sargent and Yale format also available.

Anti-Microbial Coating available in US32D Only. Use part # "ANTB-TRIM" when ordering.

FOR ELECTRIFICATION OPTION: SPECIFY ITEM # UPON ORDERING

TO ORDER "RL" OR "TS" LEVER DESIGN, REPLACE "HD" WITH "RL" OR "TS".

ITEM#	DESCRIPTION
FS12HD	FAIL-SAFE (FS) OPTION 12V AC / DC
FS24HD	FAIL-SAFE (FS) OPTION 24V AC / DC
FSE12HD	FAIL-SECURE (FSE) OPTION 12V AC / DC
FSE24HD	FAIL-SECURE (FSE) OPTION 24V AC / DC