

McKinney TA314

Three Knuckle Standard Weight Hinge



SPECIFICATIONS:

MATERIAL:

Stainless

DESCRIPTION:

Three Knuckle Standard
Weight Hinge

FASTENERS:

- (8) 1/2" x #12-24
Machine Screws
- (8) 1 1/4" x #12 Wood Screws

OPTIONS:

- NRP–Non-Removable Pin
- RC–Round Corner – 1/4" radius furnished unless specified otherwise
- HT–Hospital Tip
- SSF–Safety Stud Feature
- QC–4, 8, or 12 wire available
- CC–4, 8, or 12 wire available
- CC-18–2, 4, 6, 8, or 10 wire available (2-18AWG wires and the remainder 28AWG wires)
- MM–Magnetic Monitoring
- FT–Flat Decorative Tip
- BT–Ball Tip
- RT–Round Tip
- GT–Grooved Tip
- LT–Lined Tip
- ST–Steeple Tip

SIZE:

5" x 4 1/2"

AVAILABLE FINISHES:

- US10B/613
- US26/625
- US26D/626
- US32/629
- US32D/630
- BSP–(Black Suede Powder Coat)
- WSP–(White Suede Powder Coat)

PACKAGED/WEIGHT:

- 3 ea Per Box
- 24 ea Per Case
- Case Weight–36 lbs

UL / ANSI:

SS NFPA 80 UL Openings
A5112 Grade 2