

Lifestyle ClimbMill

LED CONSOLE

C-LS-LED

Created for low-volume facilities, our Lifestyle ClimbMill features a compact design that makes it possible to bring climbing workouts to facilities with lower ceilings. Smart features make workouts comfortable and secure, and our durable components will keep your people climbing for years. It's even as easy to service as it is to use, so it will always be ready.



Virtually anyone can step up to our LED Console and enjoy the easy navigation of the interface. Complete, easy-to-read workout feedback helps members gauge performance at a glance.

CONSOLE	
DISPLAY	Large number LED with message center
WORKOUTS	Go, manual, interval training, fat burn, rolling hills, target heart rate, glute training†, fitness tests †Some of these programs may not be
	available on this frame.
IFIT ON-DEMAND WORKOUTS	No
LANGUAGES	English, German, French, Italian, Spanish, Dutch, Portuguese, Swedish, Finnish, Turkish, Danish, Polish
FAN	No
ANALOG TV	Optional; attachable add-on TV
DIGITAL TV	Optional; attachable add-on TV
IPTV	No
PRO:IDIOM COMPATIBILITY	Optional; attachable add-on Pro:Idiom TV (≠ IPTV)
WIFI	Optional; included with Asset Management and Workout Tracking Network App
BLUETOOTH	No
ANT+	No
RFID WIRELESS LOGIN	Optional
CONNECTS TO APPLE WATCH	No
MADE FOR IPHONE®, IPAD®, IPOD®	No
CONNECTS TO SAMSUNG GALAXY WATCH	No

USB PORT	Yes; device charging, software updates
WIRELESS CHARGING (QI)	No
CSAFE READY	Yes
AUTO WAKE-UP	No

HANDLEBAR DESIGN ETHERNET CONNECTIVITY Pes Clutched ECB with industrial-grade drive chain and belt LOCKING STAIRCASE MAXIMUM USER WEIGHT CONTACT & TELEMETRIC HR CONTROL ZONE ASSEMBLED DIMENSIONS 160 x 72 x 208 cm / 63.1" x 28.2" x 81.7" STEP DIMENSIONS 23 x 40.2 x 14.3 cm / 9" x 15.8" x 5.6" MINIMUM USER WEIGHT 45 kg / 99 lbs. POWER REQUIREMENTS 100-240 V — 50/60Hz AC STEP-ON HEIGHT 26.7 cm / 10.5" SERVICE CASTER NO RESISTANCE LEVELS 30 SHIPPING WEIGHT 164.1 kg / 361.8 lbs. TOP-DOWN LEVELERS NO ASSEMBLED WEIGHT 147.1 kg / 324.4 lbs.	FRAME	
DRIVE SYSTEM Clutched ECB with industrial-grade drive chain and belt LOCKING STAIRCASE Yes MAXIMUM USER WEIGHT 136 kg / 300 lbs. CONTACT & TELEMETRIC HR CONTROL ZONE NO ASSEMBLED DIMENSIONS 160 x 72 x 208 cm / 63.1" x 28.2" x 81.7" STEP DIMENSIONS 23 x 40.2 x 14.3 cm / 9" x 15.8" x 5.6" MINIMUM USER WEIGHT 45 kg / 99 lbs. POWER REQUIREMENTS 100-240 V — 50/60Hz AC STEP-ON HEIGHT 26.7 cm / 10.5" SERVICE CASTER NO RESISTANCE RANGE 24-160 SPM RESISTANCE LEVELS 30 SHIPPING WEIGHT 164.1 kg / 361.8 lbs. TOP-DOWN LEVELERS No	HANDLEBAR DESIGN	Side
Description	ETHERNET CONNECTIVITY	Yes
MAXIMUM USER WEIGHT 136 kg / 300 lbs. CONTACT & TELEMETRIC HR Yes CONTROL ZONE No ASSEMBLED DIMENSIONS 160 x 72 x 208 cm / 63.1" x 28.2" x 81.7" STEP DIMENSIONS 23 x 40.2 x 14.3 cm / 9" x 15.8" x 5.6" MINIMUM USER WEIGHT 45 kg / 99 lbs. POWER REQUIREMENTS 100-240 V - 50/60Hz AC STEP-ON HEIGHT 26.7 cm / 10.5" SERVICE CASTER No RESISTANCE RANGE 24-160 SPM RESISTANCE LEVELS 30 SHIPPING WEIGHT 164.1 kg / 361.8 lbs. TOP-DOWN LEVELERS No	DRIVE SYSTEM	
CONTACT & TELEMETRIC HR CONTROL ZONE NO ASSEMBLED DIMENSIONS 160 x 72 x 208 cm / 63.1" x 28.2" x 81.7" STEP DIMENSIONS 23 x 40.2 x 14.3 cm / 9" x 15.8" x 5.6" MINIMUM USER WEIGHT 45 kg / 99 lbs. POWER REQUIREMENTS 100-240 V — 50/60Hz AC STEP-ON HEIGHT 26.7 cm / 10.5" SERVICE CASTER NO RESISTANCE RANGE 24-160 SPM RESISTANCE LEVELS 30 SHIPPING WEIGHT 164.1 kg / 361.8 lbs. TOP-DOWN LEVELERS No	LOCKING STAIRCASE	Yes
CONTROL ZONE No ASSEMBLED DIMENSIONS 160 x 72 x 208 cm / 63.1" x 28.2" x 81.7" STEP DIMENSIONS 23 x 40.2 x 14.3 cm / 9" x 15.8" x 5.6" MINIMUM USER WEIGHT 45 kg / 99 lbs. POWER REQUIREMENTS 100–240 V — 50/60Hz AC STEP-ON HEIGHT 26.7 cm / 10.5" SERVICE CASTER No RESISTANCE RANGE 24–160 SPM RESISTANCE LEVELS 30 SHIPPING WEIGHT 164.1 kg / 361.8 lbs. TOP-DOWN LEVELERS No	MAXIMUM USER WEIGHT	136 kg / 300 lbs.
ASSEMBLED DIMENSIONS 160 x 72 x 208 cm / 63.1" x 28.2" x 81.7" STEP DIMENSIONS 23 x 40.2 x 14.3 cm / 9" x 15.8" x 5.6" MINIMUM USER WEIGHT 45 kg / 99 lbs. POWER REQUIREMENTS 100–240 V — 50/60Hz AC STEP-ON HEIGHT 26.7 cm / 10.5" SERVICE CASTER NO RESISTANCE RANGE 24–160 SPM RESISTANCE LEVELS 30 SHIPPING WEIGHT 164.1 kg / 361.8 lbs. TOP-DOWN LEVELERS No	CONTACT & TELEMETRIC HR	Yes
81.7" STEP DIMENSIONS 23 x 40.2 x 14.3 cm / 9" x 15.8" x 5.6" MINIMUM USER WEIGHT 45 kg / 99 lbs. POWER REQUIREMENTS 100–240 V — 50/60Hz AC STEP-ON HEIGHT 26.7 cm / 10.5" SERVICE CASTER No RESISTANCE RANGE 24–160 SPM RESISTANCE LEVELS 30 SHIPPING WEIGHT 164.1 kg / 361.8 lbs. TOP-DOWN LEVELERS No	CONTROL ZONE	No
MINIMUM USER WEIGHT 45 kg / 99 lbs. POWER REQUIREMENTS 100–240 V — 50/60Hz AC STEP-ON HEIGHT 26.7 cm / 10.5" SERVICE CASTER No RESISTANCE RANGE 24–160 SPM RESISTANCE LEVELS 30 SHIPPING WEIGHT 164.1 kg / 361.8 lbs. TOP-DOWN LEVELERS No	ASSEMBLED DIMENSIONS	
POWER REQUIREMENTS 100–240 V — 50/60Hz AC STEP-ON HEIGHT 26.7 cm / 10.5" SERVICE CASTER No RESISTANCE RANGE 24–160 SPM RESISTANCE LEVELS 30 SHIPPING WEIGHT 164.1 kg / 361.8 lbs. TOP-DOWN LEVELERS No	STEP DIMENSIONS	23 x 40.2 x 14.3 cm / 9" x 15.8" x 5.6"
STEP-ON HEIGHT 26.7 cm / 10.5" SERVICE CASTER No RESISTANCE RANGE 24–160 SPM RESISTANCE LEVELS 30 SHIPPING WEIGHT 164.1 kg / 361.8 lbs. TOP-DOWN LEVELERS No	MINIMUM USER WEIGHT	45 kg / 99 lbs.
SERVICE CASTER No RESISTANCE RANGE 24–160 SPM RESISTANCE LEVELS 30 SHIPPING WEIGHT 164.1 kg / 361.8 lbs. TOP-DOWN LEVELERS No	POWER REQUIREMENTS	100-240 V — 50/60Hz AC
RESISTANCE RANGE 24–160 SPM RESISTANCE LEVELS 30 SHIPPING WEIGHT 164.1 kg / 361.8 lbs. TOP-DOWN LEVELERS No	STEP-ON HEIGHT	26.7 cm / 10.5"
RESISTANCE LEVELS 30 SHIPPING WEIGHT 164.1 kg / 361.8 lbs. TOP-DOWN LEVELERS No	SERVICE CASTER	No
SHIPPING WEIGHT 164.1 kg / 361.8 lbs. TOP-DOWN LEVELERS No	RESISTANCE RANGE	24-160 SPM
TOP-DOWN LEVELERS No	RESISTANCE LEVELS	30
	SHIPPING WEIGHT	164.1 kg / 361.8 lbs.
ASSEMBLED WEIGHT 147.1 kg / 324.4 lbs.	TOP-DOWN LEVELERS	No
	ASSEMBLED WEIGHT	147.1 kg / 324.4 lbs.