

Performance Plus Treadmill

LED CONSOLE

T-PP-LED

Our exceptional treadmill sets a new standard with a shock-absorbing slat-belt and a powerful drive system that make even the most intense runs feel comfortable, solid and smooth, lasting up to 100,000 miles in the most intense environments. Despite this incredible evolution of technology, service and maintenance have never been easier.



Virtually anyone can step up to our LED Console and enjoy the easy navigation of the interface. Complete, easy-to-read workout feedback helps members gauge performance at a glance.

CONSOLE	
DISPLAY	Large number LED with message center
WORKOUTS	Go, manual, interval training, fat burn, rolling hills, target heart rate, glute training†, fitness tests †Some of these programs may not be available on this frame.
IFIT ON-DEMAND WORKOUTS	No
LANGUAGES	English, German, French, Italian, Spanish, Dutch, Portuguese, Swedish, Finnish, Turkish, Danish, Polish
FAN	No
ANALOG TV	Optional; attachable add-on TV
DIGITAL TV	Optional; attachable add-on TV
IPTV	No
PRO:IDIOM COMPATIBILITY	Optional; attachable add-on Pro:Idiom TV (≠ IPTV)
WIFI	Optional; included with Asset Management and Workout Tracking Network App
BLUETOOTH	No
ANT+	No
RFID WIRELESS LOGIN	Optional
CONNECTS TO APPLE WATCH	No
MADE FOR IPHONE®, IPAD®, IPOD®	No
CONNECTS TO SAMSUNG GALAXY WATCH	No
USB PORT	Yes; device charging, software updates

WIRELESS CHARGING (QI)	No
CSAFE READY	Yes
AUTO WAKE-UP	No
FRAME	
TREAD SENSE	Yes
SPEED RANGE	0.8–26 km/h / 0.5–16 mph
STEP-ON HEIGHT	25 cm / 10.5"
RUNNING SURFACE TYPE	Slat belt
SERVICE CASTER	Yes
MAX USER WEIGHT	227 kg / 500 lbs.
POWER REQUIREMENTS	20 A dedicated circuit required, non-looped grounded
RUNNING SURFACE AREA	157 x 61 cm / 62" x 24"
ASSEMBLED DIMENSIONS	227 x 92.6 x 168.9 cm / 89.4" x 36.5" x 66.5"
CAST ALUMINUM END CAPS	Yes
CONTACT & TELEMETRIC HR	Yes
CROSSBAR CONTROLS	Yes
CUSHIONING SYSTEM	Pure Stride
DRIVE SYSTEM	2.2 kW PMSM Synchronous Response Drive System
ETHERNET CONNECTIVITY	Yes
HANDLEBAR DESIGN	Continuous multi-grip design
INCLINE RANGE	0–20% (1,650-lb. thrust-elevation motor)
ASSEMBLED WEIGHT	217.6 kg / 479.7 lbs.
SHIPPING WEIGHT	244.4 kg / 538.8 lbs.