

## Ø200 mm LED Traffic Lights Model No.: TP200x5PL



Novel design with beautiful appearance  
Low power consumption  
High efficiency and brightness  
Large viewing angle  
Long lifespan: 80 000 hours  
Multi-layer sealed and waterproof

### Product Features

Long viewing distance  
Visual distance:  $\geq 400\text{m}$   
Housing: GE UV resistance Polycarbonate  
Signal Module: Light-weighted with ultrathin design, Multi-layer sealed, water and dust proof, anti-vibration, Exclusive

optical lens and good color uniformity  
Wide temperature:  $-40^{\circ}\text{C}\sim+80^{\circ}\text{C}$   
Sun visor: Polycarbonate  
CE, IP55, ITE Standard, RoHS, TUV, UL, EMC, LVD, WEEE, Swedish standard SS-EN 12368:2006

### Technical Parameters:

Article Number	Color	LED Qty	Light Intensity	Wave Length	Viewing Angle L/R	Viewing Angle U/D	Power	Working Voltage	Housing Material
TP200x5PL	Red	90	$\leq 400\text{cd}$	$625\pm 5\text{ nm}$	30°	30°	6W	11-30VDC/VAC 85V-265VAC, 50/60HZ	PC, UV resistant
	Yellow		$\leq 400\text{cd}$	$590\pm 2\text{ nm}$			5W		
	Green	38	$\leq 600\text{cd}$	$505\pm 2\text{ nm}$					

### Packing Info:

Carton Size	QTY	GW	NW	Wrapper	Volume (m3)
1,42 * 0,33 * 0,23 m	1 pcs /carton box	12,50 kg	14,0 kg	K=K carton	0,11

### Packing List:

Name	Light	L Bracket	Sun Visor	M4×10 Screw	M4×20 Screw	Terminal Cover & Terminal Cover Gasket	Using Manual
Qty. (pcs)	5	2	5	20	4	1	1

**Address**  
Baiona AB  
Hagagatan 34  
113 47 Stockholm  
Sweden  
**Phone**  
+46 (0)73-679 35 50

**Company headquarters**  
Stockholm  
**Bank**  
Handelsbanken  
**IBAN**  
SE78 6000 0000 0005 9016 1881  
**BIC**  
HANDSESS

**Bankgiro**  
5456-5197  
**Organization no**  
559243-2479  
**VAT number**  
SE559243247901  
**Holds F-tax certificate**

**Internet**  
[www.ledochled.se](http://www.ledochled.se)  
**E-mail**  
[info@ledochled.se](mailto:info@ledochled.se)  
**Terms & delivery conditions**  
[www.ledochled.se/villkor](http://www.ledochled.se/villkor)