

PRODUCT INFORMATION

Product: **PF 15 PV3/60/UV**

Articlenumber: **1078903**

<u>Description of the Product</u>	Film backing:	Polyethylene
	Colour:	transparent, colourless
	Adhesive type:	Acrylic

<u>Technical data</u>	Thickness:	60 µ	(QMP 21)*
	Peel adhesion to stainless steel:	1,9 +/-0,5 N/cm	(QMP 02)*
	Breaking strength:***		(QMP 03)*
	Machine Direction (MD):	>17 N/mm ²	
	Transverse Direction (TD):	>11 N/mm ²	
	Elongation at break***		
	Machine Direction (MD):	>180 %	
	Transverse Direction (TD):	>380 %	

Application The film **PF 15 PV3/60/UV** is recommended for the protection of sensitive surfaces against dirt and damage during processing, storage and mounting, e. g.

- medium and rough structured surfaces
- front plaster
- artificial stone covering, ceramic covering
- textile floor covering
- PVC-surfaces (not weather-beaten)
- varnished metallic-, plastic- or wooden-surfaces
- glass (not with strong UV-stress)
- Aluminium anodized (Eloxal), zinc, copper, steel

Application conditions

- The surface must be free from oil, fat, dust and solvents
- Room temperature (> 10°C and < 40°C)

Resistance

- against moisture:	good
- against oil:	moderate
- against solvents:	moderate
- against UV:	300 hrs QUV-test (QMP 48)**

Storage conditions

- Room temperature < 40°C
- Storage time max. 6 months after date of production

* QMP: internal method of measurement

** 300hrs QUV-test conform to 6 months outside exposure at Wipperfürth / Westeurope climate.

*** raw filmdata

Note: The data and recommendations are given in good faith, on the basis of practical experience, but without warranty. The customer should carry out own tests to confirm the usefulness of the product for the application under consideration.