

Technical data sheet

7983 siasponge flex






MKP person responsible:	Nico Wolfrum
Serie-Verantwortlicher:	
Status:	Ok
Approval:	24.10.2016

Classification	Public series
Product type:	Foam abrasives
Haupt-Industrien:	Automotive Building Interior
Weitere-Industrien:	Kitchens Marine Windows and Doors

Product profile	
Grit type:	Aluminium oxide
Grit range (total):	60; 100; 180-220; 280
Backing:	PU foam (soft)
Coating:	Mechanical
bonding:	Elastic binder
Special coating:	
Equipment:	

Properties	Technology
Cut:	5 - medium
Lifetime:	9 - very long
Finishing:	8 - good
Flexibility:	10 - highly flexible
Contact pressure:	5 - medium

Conversion forms	Upper conversion	Lower conversion
	Foam abrasives	- Pads - Discs

Application	Superordinate group	Subgroup
	Portable machine sanding	● random orbital sander
	Manual sanding	● Manual sanding
Cut:	Dry applicationWet sanding	



Details	
No suitability for:	
Sanding recommendation:	
Safety recommendation:	- Use an effective dust extraction unit or wear a fine dust mask

Communication	
Claim:	adapts perfectly to the workpiece
Copy:	Be it curves, shapes or contours – an even and perfect sanding pattern can be achieved with 7983 siasponge flex. The extra-soft foam of siasponge flex ensures maximum conformability.
Image material:	Product Top View (PTV) Front side: ID Reverse side: ID
	Application image
	Product show:
	Macro shot: ID 8197
	Packaging image:
	Product group image: ID 8154 ID 7264

- Main application
- Secondary application