

WS LS *SERIES2*



NEXT-LEVEL PERFORMANCE

designed by *pininfarina*





WS LS

SERIES 2

NEXT-LEVEL PERFORMANCE

designed by *pininfarina*

Series 2: another step towards perfection. ANEST IWATA has revolutionized the industry once again with the release of its Series 2 Spray Guns. Engineered for superior performance with any coating, ANEST IWATA Series 2 Spray Guns are equipped with Split Nozzle™ 2.0 Technology that features optimized dual-atomization. Achieve a controlled uniform flat finish with repeatable results, all while experiencing less fatigue, fewer passes and a high transfer efficiency rate with unmatched material savings.

- Exclusive Split Nozzle™ 2.0 Technology features increased air flow passageways and a dual thread design that locks our unique Split Nozzle™ into the spray gun the same every time. This optimizes our dual-atomization, which directs air into the stream of material pre-atomizing it and forming the unique ANEST IWATA fan pattern.
- The new ANEST IWATA Split Nozzle™ 2.0 Fan Pattern is optimized with a consistent shape from top to bottom and an even distribution of droplets resulting in a controlled uniform flat finish with repeatable results.
- Designed by Pininfarina to offer the best in ergonomics and style, Series 2 is more advanced than ever. Engineered to reduce user fatigue, users will notice a better balance and weight distribution, a soft and responsive trigger engagement and easy to adjust knobs, resulting in ultimate performance and comfort.
- Optional DPG1 high-performance digital pressure regulator allows air adjustment convenience without disrupting the spray gun ergonomics. Our patented Click-Mag™ Locking System makes it easy to detach and reinstall the DPG1 to change batteries and for general spray gun maintenance.

SERIES 2
EXCLUSIVE **SPLIT**
NOZZLE 2.0



LS-400 SERIES 2 BASE



WS-400 SERIES 2 BASE



WS-400 SERIES 2 CLEAR

LS400

SERIES 2 BASE

The ANEST IWATA LS-400 Series 2 Base is a premium HVLP spray gun featuring optimized, uniform coarse atomization — perfect for solvent or waterborne base coat applications with a variety of nozzles, giving it the ability to perform in all climates and conditions.



STANDARD



DIGITAL

SERIES 2 EXCLUSIVE SPLIT NOZZLE 2.0

LS-400 SERIES 2 BASE HVLP	order info*	digital	Ø mm	application speed	no.	bar/psi	mℓ/min	CFM	mm/in
ET: FOR STANDARD CLIMATE APPLICATION									
LS-400-SR2D-1206	2912D	Y	1.2 ET	CONTROL	LS-400-06	1.8/26	165	14.1	230/9.1
LS-400-SR2-1206	2912			STANDARD			175		235/9.3
LS-400-SR2D-1306	2913D	Y	1.3 ET	SPEED			185		240/9.4
LS-400-SR2-1306	2913						190		245/9.6
LS-400-SR2D-1406	2914D	Y	1.4 ET	HIGH SPEED					
LS-400-SR2-1406	2914								
LS-400-SR2D-1506	2915D	Y	1.5 ET						
LS-400-SR2-1506	2915								
ETS: FOR HOT/DRY CLIMATE APPLICATION									
LS-400-SR2D-12S06	2912SD	Y	1.2 ETS	CONTROL	LS-400-06	1.8/26	160	14.8	200/7.9
LS-400-SR2-12S06	2912S			STANDARD			170		205/8.1
LS-400-SR2D-13S06	2913SD	Y	1.3 ETS	SPEED			185		210/8.3
LS-400-SR2-13S06	2913S						195		215/8.5
LS-400-SR2D-14S06	2914SD	Y	1.4 ETS	HIGH SPEED					
LS-400-SR2-14S06	2914S								
LS-400-SR2D-15S06	2915SD	Y	1.5 ETS						
LS-400-SR2-15S06	2915S								

*Available only as Eco Set with Gravity Spray Gun + PCG7D2 - 700 ml

WS400

SERIES 2 BASE

The compliant ANEST IWATA WS-400 Series 2 Base was designed with the future of wet-on-wet waterborne technologies in mind by delivering a faster, coarse, center wet core with optimal material control. It's offered in a variety of configurations allowing you to match your spray gun to your specific product line and environment.



STANDARD



DIGITAL

SERIES 2 EXCLUSIVE SPLIT NOZZLE 2.0

WS-400 SERIES 2 BASE COMPLIANT	order info*	digital	ø mm	climate	no.	bar/psi	mL/min	CFM	mm/in
OBS: FOR TYPE A WET ON WET APPLICATION									
WS-400-SR2D-OBS-0	2916D	Y	1.3 OBS-0	HUMID	WS-400-02-OBS	2.0/29	210	13.1	255/10.0
WS-400-SR2-OBS-0	2916			STANDARD**					215
WS-400-SR2D-OBS	2917D	Y	1.3 OBS				235		260/10.2
WS-400-SR2-OBS	2917								
WS-400-SR2D-OBS+1	2918D	Y	1.3 OBS+1	DRY					
WS-400-SR2-OBS+1	2918								
BF: FOR TYPE B WET ON WET APPLICATION									
WS-400-SR2D-BF-S	2920D	Y	BF-S	STANDARD*	WS-400-03-BF	2.0/29	245	13.1	250/9.8
WS-400-SR2-BF-S	2920								

*Available only as Eco Set with Gravity Spray Gun + PGG7D2 - 700 ml

**Standard climate range: 59-86° F (15-30°C) with a humidity of 30%-75% RH

WS400

SERIES 2 CLEAR

The compliant ANEST IWATA WS-400 Series 2 Clear is the new standard for clear coat perfection with its fast, high-delivery fine atomization. This spray gun makes achieving anything from an OEM finish to a perfect glass-like finish easy while saving materials, time, and energy.



STANDARD



DIGITAL

SERIES 2 EXCLUSIVE SPLIT NOZZLE 2.0

WS-400 SERIES 2 CLEAR COMPLIANT	order info*	digital	Ø mm	application speed	no.	bar/psi	m ³ /min	CFM	mm/in
HD: HIGH DELIVERY									
WS-400-SR2D-12HD	2712D	Y	1.2 HD	CONTROL	WS-400-03	2.0/29	220	13.1	245/9.6
WS-400-SR2-12HD	2712			STANDARD			245		250/9.8
WS-400-SR2D-13HD	2713D	Y	1.3 HD	SPEED			260		255/10.0
WS-400-SR2-13HD	2713						280		260/10.2
WS-400-SR2D-14HD	2714D	Y	1.4 HD	HIGH SPEED					
WS-400-SR2-14HD	2714								
WS-400-SR2D-15HD	2715D	Y	1.5 HD						
WS-400-SR2-15HD	2715								

*Available only as Eco Set with Gravity Spray Gun + PGG7D2 - 700 ml



ANESTIWATA.COM

#TeamIwata



SPRAYFISH^{INC} 

Kevin Backman
(360) 391-8411
kevin@sprayfishinc.com



ANEST IWATA Americas, Inc.
9525 Glades Dr, West Chester, Ohio 45011
Toll Free: (800) 470-7068 | questions@anestiwata.com
ANESTIWATA.com